

2-2. Specifications of Performance When Each Indoor Unit is Combined with Other Unit

Outdoor Unit : RAS-5M34UAV-E1

<Cooling / 220V>

Power supply (V)	Operating Status	Indoor unit					Unit Capacity					Total			Outdoor noise (dB)	
		A	B	C	D	E	A	B	C	D	E	Cooling capacity (kW)	Power consumption (W)	Operating current (A)	Sound Pressure	Sound Power
220	1 unit	07	—	—	—	—	2.0	—	—	—	—	2.0 (1.4-2.5)	650 (640- 700)	3.84 (3.83- 3.74)	51	66
		10	—	—	—	—	2.7	—	—	—	—	2.7 (1.4-3.2)	750 (640- 950)	4.43 (3.83- 4.64)	51	66
		13	—	—	—	—	3.7	—	—	—	—	3.7 (1.4-4.4)	1200 (640-1520)	6.20 (3.68- 7.20)	51	66
		16	—	—	—	—	4.5	—	—	—	—	4.5 (1.4-5.0)	1650 (640-2000)	7.98 (3.68- 9.28)	51	66
		18	—	—	—	—	5.0	—	—	—	—	5.0 (1.4-5.2)	1950 (640-2100)	9.33 (3.68- 9.74)	51	66
		22	—	—	—	—	6.0	—	—	—	—	6.0 (2.4-6.8)	2020 (640-2500)	9.56 (3.68-11.60)	51	66
		24	—	—	—	—	7.1	—	—	—	—	7.1 (2.4-7.2)	2390 (660-2960)	11.32 (3.80-13.73)	51	66
	2 units	07	07	—	—	—	2.00	2.00	—	—	—	4.0 (2.5-5.0)	1520 (640-1770)	7.27 (3.64- 8.21)	51	66
		10	07	—	—	—	2.70	2.00	—	—	—	4.7 (2.5-5.7)	1530 (640-1910)	7.32 (3.64- 8.86)	51	66
		13	07	—	—	—	3.70	2.00	—	—	—	5.7 (2.6-6.5)	1810 (660-2130)	8.66 (3.75- 9.88)	51	66
		16	07	—	—	—	4.08	1.82	—	—	—	5.9 (2.7-6.6)	1810 (660-2220)	8.66 (3.75-10.30)	51	66
		18	07	—	—	—	4.50	1.80	—	—	—	6.3 (2.9-6.9)	2040 (670-2400)	9.76 (3.81-11.13)	51	66
		22	07	—	—	—	4.73	1.58	—	—	—	6.3 (2.9-6.9)	2040 (670-2400)	9.76 (3.81-11.13)	51	66
		24	07	—	—	—	5.31	1.49	—	—	—	6.8 (3.0-7.2)	2320 (690-2570)	11.10 (3.92-11.92)	51	66
		10	10	—	—	—	2.70	2.70	—	—	—	5.4 (2.5-6.3)	1530 (640-2040)	7.32 (3.64- 9.46)	51	66
		13	10	—	—	—	3.41	2.49	—	—	—	5.9 (2.7-6.6)	1810 (660-2220)	8.66 (3.75-10.30)	51	66
		16	10	—	—	—	3.94	2.36	—	—	—	6.3 (2.9-6.9)	2040 (670-2400)	9.76 (3.81-11.13)	51	66
		18	10	—	—	—	4.09	2.21	—	—	—	6.3 (2.9-6.9)	2040 (670-2400)	9.76 (3.81-11.13)	51	66
		22	10	—	—	—	4.69	2.11	—	—	—	6.8 (3.0-7.2)	2320 (690-2570)	11.10 (3.92-11.92)	51	66
		24	10	—	—	—	5.22	1.98	—	—	—	7.2 (3.2-7.5)	2550 (700-2750)	12.20 (3.98-12.76)	51	66
		13	13	—	—	—	3.15	3.15	—	—	—	6.3 (2.9-6.9)	2040 (670-2400)	9.76 (3.81-11.13)	51	66
		16	13	—	—	—	3.73	3.07	—	—	—	6.8 (3.0-7.2)	2320 (690-2570)	11.10 (3.92-11.92)	51	66
		18	13	—	—	—	3.91	2.89	—	—	—	6.8 (3.0-7.2)	2320 (690-2570)	11.10 (3.92-11.92)	51	66
		22	13	—	—	—	4.45	2.75	—	—	—	7.2 (3.2-7.5)	2550 (700-2750)	12.20 (3.98-12.76)	51	66
		24	13	—	—	—	4.73	2.47	—	—	—	7.2 (3.2-7.5)	2550 (700-2750)	12.20 (3.98-12.76)	51	66
		16	16	—	—	—	3.60	3.60	—	—	—	7.2 (3.2-7.5)	2550 (700-2750)	12.20 (3.98-12.76)	51	66
		18	16	—	—	—	3.79	3.41	—	—	—	7.2 (3.2-7.5)	2550 (700-2750)	12.20 (3.98-12.76)	51	66
		22	16	—	—	—	4.17	3.13	—	—	—	7.3 (3.2-7.5)	2550 (700-2750)	12.20 (3.98-12.76)	51	66
		24	16	—	—	—	4.47	2.83	—	—	—	7.3 (3.2-7.5)	2550 (700-2750)	12.20 (3.98-12.76)	51	66
		18	18	—	—	—	3.60	3.60	—	—	—	7.2 (3.2-7.5)	2550 (700-2750)	12.20 (3.98-12.76)	51	66
		22	18	—	—	—	4.04	3.36	—	—	—	7.4 (3.2-7.5)	2550 (700-2750)	12.20 (3.98-12.76)	51	66
		24	18	—	—	—	4.34	3.06	—	—	—	7.4 (3.2-7.5)	2550 (700-2750)	12.20 (3.98-12.76)	51	66
		22	22	—	—	—	4.00	4.00	—	—	—	8.0 (3.2-8.3)	2170 (700-2370)	10.27 (3.98-10.99)	51	66
		24	24	—	—	—	3.66	4.34	—	—	—	8.0 (3.2-8.3)	2170 (700-2370)	10.27 (3.98-10.99)	51	66
		24	24	—	—	—	4.05	4.05	—	—	—	8.1 (3.2-8.4)	2200 (700-2400)	10.42 (3.98-11.13)	51	66
	3 units	07	07	07	—	—	2.00	2.00	2.00	—	—	6.0 (3.8-7.5)	2400 (950-2720)	11.48 (4.80-12.62)	51	66
		10	07	07	—	—	2.70	2.00	2.00	—	—	6.7 (3.8-8.2)	2400 (950-2720)	11.48 (4.80-12.62)	51	66
		13	07	07	—	—	3.65	1.97	1.97	—	—	7.6 (3.9-8.3)	2410 (960-2740)	11.53 (4.85-12.71)	51	66
		16	07	07	—	—	4.08	1.81	1.81	—	—	7.7 (4.0-8.5)	2410 (960-2790)	11.53 (4.85-12.94)	51	66
		18	07	07	—	—	4.28	1.71	1.71	—	—	7.7 (4.0-8.5)	2410 (960-2790)	11.53 (4.85-12.94)	51	66
		22	07	07	—	—	4.68	1.56	1.56	—	—	7.8 (4.1-8.6)	2430 (970-2810)	11.63 (4.90-13.03)	51	66
		24	07	07	—	—	4.99	1.41	1.41	—	—	7.8 (4.1-8.6)	2430 (970-2810)	11.63 (4.90-13.03)	51	66
		10	10	07	—	—	2.70	2.70	2.00	—	—	7.4 (3.8-8.2)	2400 (950-2720)	11.48 (4.80-12.62)	51	66
		13	10	07	—	—	3.39	2.48	1.83	—	—	7.7 (3.9-8.3)	2410 (960-2740)	11.53 (4.85-12.71)	51	66
		16	10	07	—	—	3.77	2.26	1.67	—	—	7.7 (4.0-8.5)	2410 (960-2790)	11.53 (4.85-12.94)	51	66
		18	10	07	—	—	3.97	2.14	1.59	—	—	7.7 (4.0-8.5)	2410 (960-2790)	11.53 (4.85-12.94)	51	66
		22	10	07	—	—	4.37	1.97	1.46	—	—	7.8 (4.1-8.6)	2430 (970-2810)	11.63 (4.90-13.03)	51	66
		24	10	07	—	—	4.69	1.78	1.32	—	—	7.8 (4.1-8.6)	2430 (970-2810)	11.63 (4.90-13.03)	51	66
		13	13	07	—	—	3.03	3.03	1.64	—	—	7.7 (4.0-8.5)	2410 (960-2790)	11.53 (4.85-12.94)	51	66
		16	13	07	—	—	3.44	2.83	1.53	—	—	7.8 (4.1-8.6)	2430 (970-2810)	11.63 (4.90-13.03)	51	66
		18	13	07	—	—	3.64	2.70	1.46	—	—	7.8 (4.1-8.6)	2430 (970-2810)	11.63 (4.90-13.03)	51	66
		22	13	07	—	—	4.00	2.47	1.33	—	—	7.8 (4.1-8.6)	2430 (970-2810)	11.63 (4.90-13.03)	51	66
		24	13	07	—	—	4.38	2.28	1.23	—	—	7.9 (4.1-8.7)	2440 (970-2830)	11.67 (4.90-13.13)	51	66
		16	16	07	—	—	3.19	3.19	1.42	—	—	7.8 (4.1-8.6)	2430 (970-2810)	11.63 (4.90-13.03)	51	66
		18	16	07	—	—	3.39	3.05	1.36	—	—	7.8 (4.1-8.6)	2430 (970-2810)	11.63 (4.90-13.03)	51	66
		22	16	07	—	—	3.79	2.84	1.26	—	—	7.9 (4.1-8.7)	2440 (970-2830)	11.67 (4.90-13.13)	51	66
		24	16	07	—	—	4.12	2.61	1.16	—	—	7.9 (4.1-8.7)	2440 (970-2830)	11.67 (4.90-13.13)	51	66
		18	18	07	—	—	3.29	3.29	1.32	—	—	7.9 (4.1-8.7)	2440 (970-2830)	11.67 (4.90-13.13)	51	66
		22	18	07	—	—	3.65	3.04	1.22	—	—	7.9 (4.1-8.7)	2440 (970-2830)	11.67 (4.90-13.13)	51	66
		24	18	07	—	—	3.98	2.80	1.12	—	—	7.9 (4.1-8.7)	2440 (970-2830)	11.67 (4.90-13.13)	51	66
		10	10	10	—	—	2.53	2.53	2.53	—	—	7.6 (3.8-8.2)	2400 (950-2720)	11.48 (4.80-12.62)	51	66
		13	10	10	—	—	3.13	2.28	2.28	—	—	7.7 (3.9-8.3)	2410 (960-2740)	11.53 (4.85-12.71)	51	66
		16	10	10	—	—	3.50	2.10	2.10	—	—	7.7 (4.0-8.5)	2410 (960-2790)	11.53 (4.85-12.94)	51	66
		18	10	10	—	—	3.70	2.00	2.00	—	—	7.7 (4.0-8.5)	2410 (960-2790)	11.53 (4.85-12.94)	51	66
		22	10	10	—	—	4.16	1.87	1.87	—	—	7.9 (4.1-8.7)	2440 (970-2830)	11.67 (4.90-13.13)	51	66
		24	10	10	—	—	4.49	1.71	1.71	—	—	7.9 (4.1-8.7)	2440 (970-2830)	11.67 (4.90-13.13)	51	66
		13	13	10	—	—	2.82	2.82	2.06	—	—	7.7 (4.0-8.5)	2410 (960-2790)	11.53 (4.85-12.94)	51	66
		16	13	10	—	—	3.22	2.65	1.93	—	—	7.8 (4.1-8.6)	2430 (970-2810)	11.63 (4.90-13.03)	51	66
		18	13	10	—	—	3.42	2.53	1.85	—	—	7.8 (4.1-8.6)	2430 (970-2810)	11.63 (4.90-13.03)	51	66
		22	13	10	—	—	3.82	2.36	1.72	—	—	7.9 (4.1-8.7)	2440 (970-2830)	11.67 (4.90-13.13)	51	66
		24	13	10	—	—	4.15	2.17	1.58	—	—	7.9 (4.1-8.7)	2440 (970-2830)	11.67 (4.90-13.13)	51	66
		16	16	10	—	—	3.04	3.04	1.82	—	—	7.9 (4.1-8.7)	2440 (970-2830)	11.67 (4.90-13.13)	51	66
		18	16	10	—	—	3.20	2.88	1.73	—	—	7.8 (4.1-8.6)	2430 (970-2810)	11.63 (4.90-13.03)	51	66
		22	16	10	—	—	3.64	2.73	1.64	—	—	8.0 (4.3-9.0)	2450 (980-2900)	11.72 (4.95-13.45)	51	66
24		16	10	—	—	3.97	2.52	1.51	—	—	8.0 (4.3-9.0)	2450 (980-2900)	11.72 (4.95-13.45)	51	66	
18		18	10	—	—	3.11	3.11	1.68	—	—	7.9 (4.1-8.7)	2440 (970-2830)	11.67 (4.90-13.13)	51	66	
13		13	13	—	—	2.60										

<Cooling / 220V> (Continued)

Power supply (V)	Operating Status	Indoor unit					Unit Capacity					Total				Outdoor noise (dB)	
		A	B	C	D	E	A	B	C	D	E	Cooling capacity (kW)	Power consumption (W)	Operating current (A)	Sound Pressure	Sound Power	
220	4 units	07	07	07	07	—	2.00	2.00	2.00	2.00	—	8.0 (4.0-8.7)	2550 (930-2800)	12.20 (4.70-12.99)	51	66	
		10	07	07	07	—	2.61	1.93	1.93	1.93	—	8.4 (4.0-8.8)	2710 (930-2820)	12.97 (4.70-13.08)	51	66	
		13	07	07	07	—	3.28	1.77	1.77	1.77	—	8.6 (4.1-9.0)	2720 (940-2850)	13.01 (4.75-13.22)	51	66	
		16	07	07	07	—	3.73	1.66	1.66	1.66	—	8.7 (4.1-9.1)	2720 (940-2850)	13.01 (4.75-13.22)	51	66	
		18	07	07	07	—	4.00	1.60	1.60	1.60	—	8.8 (4.1-9.2)	2730 (940-2880)	13.06 (4.75-13.36)	51	66	
		22	07	07	07	—	4.45	1.48	1.48	1.48	—	8.9 (4.1-9.3)	2730 (940-2880)	13.06 (4.75-13.36)	51	66	
		24	07	07	07	—	4.88	1.37	1.37	1.37	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		10	10	07	07	—	2.44	2.44	1.81	1.81	—	8.5 (4.0-8.9)	2710 (930-2820)	12.97 (4.70-13.08)	51	66	
		13	10	07	07	—	3.10	2.26	1.67	1.67	—	8.7 (4.1-9.1)	2720 (940-2850)	13.01 (4.75-13.22)	51	66	
		16	10	07	07	—	3.54	2.12	1.57	1.57	—	8.8 (4.1-9.2)	2730 (940-2880)	13.06 (4.75-13.36)	51	66	
		18	10	07	07	—	3.80	2.05	1.52	1.52	—	8.9 (4.1-9.3)	2730 (940-2880)	13.06 (4.75-13.36)	51	66	
		22	10	07	07	—	4.25	1.91	1.42	1.42	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		24	10	07	07	—	4.63	1.76	1.30	1.30	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		13	13	07	07	—	2.89	2.89	1.56	1.56	—	8.9 (4.1-9.3)	2730 (940-2880)	13.06 (4.75-13.36)	51	66	
		16	13	07	07	—	3.32	2.73	1.48	1.48	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		18	13	07	07	—	3.54	2.62	1.42	1.42	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		22	13	07	07	—	3.94	2.43	1.31	1.31	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		24	13	07	07	—	4.32	2.25	1.22	1.22	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		16	16	07	07	—	3.12	3.12	1.38	1.38	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		18	16	07	07	—	3.33	3.00	1.33	1.33	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		22	16	07	07	—	3.72	2.79	1.24	1.24	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		24	16	07	07	—	4.10	2.60	1.15	1.15	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		18	18	07	07	—	3.21	3.21	1.29	1.29	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		22	18	07	07	—	3.60	3.00	1.20	1.20	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		24	18	07	07	—	3.97	2.80	1.12	1.12	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		10	10	10	07	—	2.30	2.30	2.30	1.70	—	8.6 (4.1-9.0)	2720 (940-2850)	13.01 (4.75-13.22)	51	66	
		13	10	10	07	—	2.93	2.14	2.14	1.59	—	8.8 (4.1-9.2)	2730 (940-2880)	13.06 (4.75-13.36)	51	66	
		16	10	10	07	—	3.37	2.02	2.02	1.50	—	8.9 (4.1-9.3)	2730 (940-2880)	13.06 (4.75-13.36)	51	66	
		18	10	10	07	—	3.63	1.96	1.96	1.45	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		22	10	10	07	—	4.03	1.81	1.81	1.34	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		24	10	10	07	—	4.41	1.68	1.68	1.24	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		13	13	10	07	—	2.75	2.75	2.01	1.49	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		16	13	10	07	—	3.14	2.58	1.88	1.40	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		18	13	10	07	—	3.36	2.49	1.81	1.34	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		22	13	10	07	—	3.75	2.31	1.69	1.25	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		24	13	10	07	—	4.12	2.15	1.57	1.16	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		16	16	10	07	—	2.96	2.96	1.77	1.31	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		18	16	10	07	—	3.17	2.85	1.71	1.27	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		22	16	10	07	—	3.55	2.66	1.60	1.18	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		24	16	10	07	—	3.92	2.48	1.49	1.10	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		18	18	10	07	—	3.06	3.06	1.65	1.22	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		22	18	10	07	—	3.44	2.87	1.55	1.15	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		24	18	10	07	—	3.80	2.68	1.45	1.07	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		13	13	13	07	—	2.54	2.54	2.54	1.37	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		16	13	13	07	—	2.91	2.40	2.40	1.29	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		18	13	13	07	—	3.13	2.31	2.31	1.25	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		22	13	13	07	—	3.51	2.16	2.16	1.17	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		24	13	13	07	—	3.87	2.02	2.02	1.09	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		16	16	13	07	—	2.76	2.76	2.27	1.22	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		18	16	13	07	—	2.96	2.66	2.19	1.18	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		22	16	13	07	—	3.33	2.50	2.06	1.11	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		24	16	13	07	—	3.69	2.34	1.92	1.04	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		18	18	13	07	—	2.87	2.87	2.12	1.15	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		22	18	13	07	—	3.23	2.69	1.99	1.08	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		24	18	13	07	—	3.59	2.53	1.87	1.01	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		10	10	10	10	—	2.18	2.18	2.18	2.18	—	8.7 (4.1-9.1)	2720 (940-2850)	13.01 (4.75-13.22)	51	66	
		13	10	10	10	—	2.79	2.04	2.04	2.04	—	8.9 (4.1-9.3)	2730 (940-2880)	13.06 (4.75-13.36)	51	66	
		16	10	10	10	—	3.21	1.93	1.93	1.93	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		18	10	10	10	—	3.44	1.85	1.85	1.85	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		22	10	10	10	—	3.83	1.72	1.72	1.72	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		24	10	10	10	—	4.20	1.60	1.60	1.60	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		13	13	10	10	—	2.60	2.60	1.90	1.90	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		16	13	10	10	—	2.98	2.45	1.79	1.79	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		22	13	10	10	—	3.58	2.21	1.61	1.61	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		24	13	10	10	—	3.94	2.06	1.50	1.50	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		16	16	10	10	—	2.81	2.81	1.69	1.69	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		18	13	10	10	—	3.19	2.36	1.72	1.72	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
		22	16	10	10	—	3.40	2.55	1.53	1.53	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66	
24	16	10	10	—	3.76	2.38	1.43	1.43	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66			
18	16	10	10	—	3.02	2.72	1.63	1.63	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66			
18	18	10	10	—	2.92	2.92	1.58	1.58	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66			
22	18	10	10	—	3.29	2.74	1.48	1.48	—	9.0 (4.2-9.4)	2740 (950-2900)	13.11 (4.80-13.45)	51	66			
24	18	10	10	—													

<Cooling / 220V> (Continued)

Power supply (V)	Operating Status	Indoor unit					Unit Capacity					Total			Outdoor noise (dB)	
		A	B	C	D	E	A	B	C	D	E	Cooling capacity (kW)	Power consumption (W)	Operating current (A)	Sound Pressure	Sound Power
220	5 units	07 07 07 07 07	1.96	1.96	1.96	1.96	1.96	1.96	1.96	1.96	1.96	9.8 (3.7-10.8)	2865 (950-3630)	13.71 (4.80-16.84)	51	66
		10 07 07 07 07	2.50	1.85	1.85	1.85	1.85	1.85	1.85	1.85	1.85	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		13 07 07 07 07	3.13	1.69	1.69	1.69	1.69	1.69	1.69	1.69	1.69	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		16 07 07 07 07	3.56	1.58	1.58	1.58	1.58	1.58	1.58	1.58	1.58	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		18 07 07 07 07	3.81	1.52	1.52	1.52	1.52	1.52	1.52	1.52	1.52	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		10 10 07 07 07	2.34	2.34	1.74	1.74	1.74	1.74	1.74	1.74	1.74	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		13 10 07 07 07	2.95	2.16	1.60	1.60	1.60	1.60	1.60	1.60	1.60	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		16 10 07 07 07	3.38	2.03	1.50	1.50	1.50	1.50	1.50	1.50	1.50	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		18 10 07 07 07	3.61	1.95	1.45	1.45	1.45	1.45	1.45	1.45	1.45	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		13 13 07 07 07	2.73	2.73	1.48	1.48	1.48	1.48	1.48	1.48	1.48	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		16 13 07 07 07	3.14	2.58	1.39	1.39	1.39	1.39	1.39	1.39	1.39	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		18 13 07 07 07	3.37	2.49	1.35	1.35	1.35	1.35	1.35	1.35	1.35	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		16 16 07 07 07	2.97	2.97	1.32	1.32	1.32	1.32	1.32	1.32	1.32	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		18 16 07 07 07	3.19	2.87	1.28	1.28	1.28	1.28	1.28	1.28	1.28	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		10 10 10 07 07	2.21	2.21	2.21	1.64	1.64	1.64	1.64	1.64	1.64	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		13 10 10 07 07	2.80	2.04	2.04	1.51	1.51	1.51	1.51	1.51	1.51	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		13 13 10 07 07	2.60	2.60	1.90	1.40	1.40	1.40	1.40	1.40	1.40	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		16 10 10 07 07	3.21	1.92	1.92	1.42	1.42	1.42	1.42	1.42	1.42	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		18 10 10 07 07	3.44	1.86	1.86	1.38	1.38	1.38	1.38	1.38	1.38	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		13 13 13 07 07	2.43	2.43	2.43	1.31	1.31	1.31	1.31	1.31	1.31	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		16 13 13 07 07	2.80	2.30	2.30	1.25	1.25	1.25	1.25	1.25	1.25	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		18 13 13 07 07	3.02	2.23	2.23	1.21	1.21	1.21	1.21	1.21	1.21	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		16 16 10 07 07	2.84	2.84	1.70	1.26	1.26	1.26	1.26	1.26	1.26	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		18 16 10 07 07	3.06	2.75	1.65	1.22	1.22	1.22	1.22	1.22	1.22	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		16 16 13 07 07	2.67	2.67	2.19	1.19	1.19	1.19	1.19	1.19	1.19	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		18 16 13 07 07	2.88	2.59	2.13	1.15	1.15	1.15	1.15	1.15	1.15	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		10 10 10 10 07	2.09	2.09	2.09	2.09	1.55	1.55	1.55	1.55	1.55	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		13 10 10 10 07	2.65	1.94	1.94	1.94	1.43	1.43	1.43	1.43	1.43	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		16 10 10 10 07	3.05	1.83	1.83	1.83	1.36	1.36	1.36	1.36	1.36	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		18 10 10 10 07	3.28	1.77	1.77	1.77	1.31	1.31	1.31	1.31	1.31	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		13 13 10 10 07	2.48	2.48	1.81	1.81	1.34	1.34	1.34	1.34	1.34	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		16 13 10 10 07	2.86	2.35	1.71	1.71	1.27	1.27	1.27	1.27	1.27	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		18 13 10 10 07	3.07	2.28	1.66	1.66	1.23	1.23	1.23	1.23	1.23	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		16 16 10 10 07	2.72	2.72	1.63	1.63	1.21	1.21	1.21	1.21	1.21	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		13 13 13 10 07	2.32	2.32	2.32	1.69	1.25	1.25	1.25	1.25	1.25	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		16 13 13 10 07	2.68	2.21	2.21	1.61	1.19	1.19	1.19	1.19	1.19	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		16 16 13 10 07	2.56	2.56	2.11	1.54	1.14	1.14	1.14	1.14	1.14	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		13 13 13 13 07	2.18	2.18	2.18	2.18	1.18	1.18	1.18	1.18	1.18	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		16 13 13 13 07	2.53	2.08	2.08	2.08	1.13	1.13	1.13	1.13	1.13	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		16 16 13 13 07	2.42	2.42	1.99	1.99	1.08	1.08	1.08	1.08	1.08	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		10 10 10 10 10	1.98	1.98	1.98	1.98	1.98	1.98	1.98	1.98	1.98	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		13 10 10 10 10	2.53	1.84	1.84	1.84	1.84	1.84	1.84	1.84	1.84	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		16 10 10 10 10	2.91	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		18 10 10 10 10	3.13	1.69	1.69	1.69	1.69	1.69	1.69	1.69	1.69	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		13 13 10 10 10	2.36	2.36	1.72	1.72	1.72	1.72	1.72	1.72	1.72	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		16 13 10 10 10	2.73	2.25	1.64	1.64	1.64	1.64	1.64	1.64	1.64	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		18 13 10 10 10	2.95	2.18	1.59	1.59	1.59	1.59	1.59	1.59	1.59	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		16 16 10 10 10	2.61	2.61	1.56	1.56	1.56	1.56	1.56	1.56	1.56	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		13 13 13 10 10	2.22	2.22	2.22	1.62	1.62	1.62	1.62	1.62	1.62	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		16 13 13 10 10	2.58	2.12	2.12	1.55	1.55	1.55	1.55	1.55	1.55	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		18 13 13 10 10	2.78	2.06	2.06	1.50	1.50	1.50	1.50	1.50	1.50	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		16 16 13 10 10	2.49	2.49	2.04	1.49	1.49	1.49	1.49	1.49	1.49	10.0 (3.7-11.0)	2923 (950-3700)	13.99 (4.80-17.16)	51	66
		13 13 13 13 10	2.09	2.09	2.09	2.09	1.53	1.53	1.53	1.53	1.53	9.9 (3.7-10.9)	2894 (950-3670)	13.85 (4.80-17.02)	51	66
		16 13 13 13 10	2.46	2.02	2.02	2.02	1.48	1.48	1.48	1.48	1.48	10.0 (3.7-11.0)	2923 (950-3700)	13.99 (4.80-17.16)	51	66
		18 13 13 13 10	2.66	1.97	1.97	1.97	1.44	1.44	1.44	1.44	1.44	10.0 (3.7-11.0)	2923 (950-3700)	13.99 (4.80-17.16)	51	66
		16 16 13 13 10	2.36	2.36	1.94	1.94	1.41	1.41	1.41	1.41	1.41	10.0 (3.7-11.0)	2923 (950-3700)	13.99 (4.80-17.16)	51	66
		13 13 13 13 13	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	10.0 (3.7-11.0)	2923 (950-3700)	13.99 (4.80-17.16)	51	66
		16 13 13 13 13	2.33	1.92	1.92	1.92	1.92	1.92	1.92	1.92	1.92	10.0 (3.7-11.0)	2923 (950-3700)	13.99 (4.80-17.16)	51	66
		22 07* 07* 07* 07*	4.29	1.43	1.43	1.43	1.43	1.43	1.43	1.43	1.43	10.0 (3.7-11.0)	2923 (950-3700)	13.99 (4.80-17.16)	51	66
		22 10* 07* 07* 07*	4.08	1.84	1.36	1.36	1.36	1.36	1.36	1.36	1.36	10.0 (3.7-11.0)	2923 (950-3700)	13.99 (4.80-17.16)	51	66
		22 10* 10* 07* 07*	3.90	1.75	1.75	1.30	1.30	1.30	1.30	1.30	1.30	10.0 (3.7-11.0)	2923 (950-3700)	13.99 (4.80-17.16)	51	66

<Cooling / 230V>

Power supply (V)	Operating Status	Indoor unit					Unit Capacity					Total			Outdoor noise (dB)	
		A	B	C	D	E	A	B	C	D	E	Cooling capacity (kW)	Power consumption (W)	Operating current (A)	Sound Pressure	Sound Power
230	1 unit	07	—	—	—	—	2.0	—	—	—	—	2.0 (1.4-2.5)	650 (640- 700)	3.67 (3.66- 3.58)	51	66
		10	—	—	—	—	2.7	—	—	—	—	2.7 (1.4-3.2)	750 (640- 950)	4.23 (3.66- 4.44)	51	66
		13	—	—	—	—	3.7	—	—	—	—	3.7 (1.4-4.4)	1200 (640-1520)	5.93 (3.52- 6.88)	51	66
		16	—	—	—	—	4.5	—	—	—	—	4.5 (1.4-5.0)	1650 (640-2000)	7.63 (3.52- 8.87)	51	66
		18	—	—	—	—	5.0	—	—	—	—	5.0 (1.4-5.2)	1950 (640-2100)	8.92 (3.52- 9.32)	51	66
		22	—	—	—	—	6.0	—	—	—	—	6.0 (2.4-6.8)	2020 (640-2500)	9.15 (3.52-11.09)	51	66
		24	—	—	—	—	7.1	—	—	—	—	7.1 (2.4-7.2)	2390 (660-2960)	10.82 (3.63-13.13)	51	66
		07	10	—	—	—	2.00	2.00	—	—	—	4.0 (2.5-5.0)	1520 (640-1770)	6.96 (3.48- 7.85)	51	66
		10	07	—	—	—	2.70	2.00	—	—	—	4.7 (2.5-5.7)	1530 (640-1910)	7.00 (3.48- 8.47)	51	66
		13	07	—	—	—	3.70	2.00	—	—	—	5.7 (2.6-6.5)	1810 (660-2130)	8.28 (3.59- 9.45)	51	66
	2 units	16	07	—	—	—	4.08	1.82	—	—	—	5.9 (2.7-6.6)	1810 (660-2220)	8.28 (3.59- 9.85)	51	66
		18	07	—	—	—	4.50	1.80	—	—	—	6.3 (2.9-6.9)	2040 (670-2400)	9.34 (3.64-10.65)	51	66
		22	07	—	—	—	4.73	1.58	—	—	—	6.3 (2.9-6.9)	2040 (670-2400)	9.34 (3.64-10.65)	51	66
		24	07	—	—	—	5.31	1.49	—	—	—	6.8 (3.0-7.2)	2320 (690-2570)	10.62 (3.75-11.40)	51	66
		10	10	—	—	—	2.70	2.70	—	—	—	5.4 (2.5-6.3)	1530 (640-2040)	7.00 (3.48- 9.05)	51	66
		13	10	—	—	—	3.41	2.49	—	—	—	5.9 (2.7-6.6)	1810 (660-2220)	8.28 (3.59- 9.85)	51	66
		16	10	—	—	—	3.94	2.36	—	—	—	6.3 (2.9-6.9)	2040 (670-2400)	9.34 (3.64-10.65)	51	66
		18	10	—	—	—	4.09	2.21	—	—	—	6.3 (2.9-6.9)	2040 (670-2400)	9.34 (3.64-10.65)	51	66
		22	10	—	—	—	4.69	2.11	—	—	—	6.8 (3.0-7.2)	2320 (690-2570)	10.62 (3.75-11.40)	51	66
		24	10	—	—	—	5.22	1.98	—	—	—	7.2 (3.2-7.5)	2550 (700-2750)	11.67 (3.80-12.20)	51	66
		13	13	—	—	—	3.15	3.15	—	—	—	6.3 (2.9-6.9)	2040 (670-2400)	9.34 (3.64-10.65)	51	66
		16	13	—	—	—	3.73	3.07	—	—	—	6.8 (3.0-7.2)	2320 (690-2570)	10.62 (3.75-11.40)	51	66
		18	13	—	—	—	3.91	2.89	—	—	—	6.8 (3.0-7.2)	2320 (690-2570)	10.62 (3.75-11.40)	51	66
		22	13	—	—	—	4.45	2.75	—	—	—	7.2 (3.2-7.5)	2550 (700-2750)	11.67 (3.80-12.20)	51	66
		24	13	—	—	—	4.73	2.47	—	—	—	7.2 (3.2-7.5)	2550 (700-2750)	11.67 (3.80-12.20)	51	66
		16	16	—	—	—	3.60	3.60	—	—	—	7.2 (3.2-7.5)	2550 (700-2750)	11.67 (3.80-12.20)	51	66
		18	16	—	—	—	3.79	3.41	—	—	—	7.2 (3.2-7.5)	2550 (700-2750)	11.67 (3.80-12.20)	51	66
		22	16	—	—	—	4.17	3.13	—	—	—	7.3 (3.2-7.5)	2550 (700-2750)	11.67 (3.80-12.20)	51	66
		24	16	—	—	—	4.47	2.83	—	—	—	7.3 (3.2-7.5)	2550 (700-2750)	11.67 (3.80-12.20)	51	66
		18	18	—	—	—	3.60	3.60	—	—	—	7.2 (3.2-7.5)	2550 (700-2750)	11.67 (3.80-12.20)	51	66
		22	18	—	—	—	4.04	3.36	—	—	—	7.4 (3.2-7.5)	2550 (700-2750)	11.67 (3.80-12.20)	51	66
		24	18	—	—	—	4.34	3.06	—	—	—	7.4 (3.2-7.5)	2550 (700-2750)	11.67 (3.80-12.20)	51	66
		22	22	—	—	—	4.00	4.00	—	—	—	8.0 (3.2-8.3)	2170 (700-2370)	9.83 (3.80-10.51)	51	66
		24	24	—	—	—	3.66	4.34	—	—	—	8.0 (3.2-8.3)	2170 (700-2370)	9.83 (3.80-10.51)	51	66
		24	24	—	—	—	4.05	4.05	—	—	—	8.1 (3.2-8.4)	2200 (700-2400)	9.96 (3.80-10.65)	51	66
	3 units	07	07	07	—	—	2.00	2.00	2.00	—	—	6.0 (3.8-7.5)	2400 (950-2720)	10.98 (4.59-12.07)	51	66
		10	07	07	—	—	2.70	2.00	2.00	—	—	6.7 (3.8-8.2)	2400 (950-2720)	10.98 (4.59-12.07)	51	66
		13	07	07	—	—	3.65	1.97	1.97	—	—	7.6 (3.9-8.3)	2410 (960-2740)	11.03 (4.64-12.16)	51	66
		16	07	07	—	—	4.08	1.81	1.81	—	—	7.7 (4.0-8.5)	2410 (960-2790)	11.03 (4.64-12.38)	51	66
		18	07	07	—	—	4.28	1.71	1.71	—	—	7.7 (4.0-8.5)	2410 (960-2790)	11.03 (4.64-12.38)	51	66
		22	07	07	—	—	4.68	1.56	1.56	—	—	7.8 (4.1-8.6)	2430 (970-2810)	11.12 (4.69-12.47)	51	66
		24	07	07	—	—	4.99	1.41	1.41	—	—	7.8 (4.1-8.6)	2430 (970-2810)	11.12 (4.69-12.47)	51	66
		10	10	07	—	—	2.70	2.70	2.00	—	—	7.4 (3.8-8.2)	2400 (950-2720)	10.98 (4.59-12.07)	51	66
		13	10	07	—	—	3.39	2.48	1.83	—	—	7.7 (3.9-8.3)	2410 (960-2740)	11.03 (4.64-12.16)	51	66
		16	10	07	—	—	3.77	2.26	1.67	—	—	7.7 (4.0-8.5)	2410 (960-2790)	11.03 (4.64-12.38)	51	66
		18	10	07	—	—	3.97	2.14	1.59	—	—	7.7 (4.0-8.5)	2410 (960-2790)	11.03 (4.64-12.38)	51	66
		22	10	07	—	—	4.37	1.97	1.46	—	—	7.8 (4.1-8.6)	2430 (970-2810)	11.12 (4.69-12.47)	51	66
		24	10	07	—	—	4.69	1.78	1.32	—	—	7.8 (4.1-8.6)	2430 (970-2810)	11.12 (4.69-12.47)	51	66
		13	13	07	—	—	3.03	3.03	1.64	—	—	7.7 (4.0-8.5)	2410 (960-2790)	11.03 (4.64-12.38)	51	66
		16	13	07	—	—	3.44	2.83	1.53	—	—	7.8 (4.1-8.6)	2430 (970-2810)	11.12 (4.69-12.47)	51	66
		18	13	07	—	—	3.64	2.70	1.46	—	—	7.8 (4.1-8.6)	2430 (970-2810)	11.12 (4.69-12.47)	51	66
		22	13	07	—	—	4.00	2.47	1.33	—	—	7.8 (4.1-8.6)	2430 (970-2810)	11.12 (4.69-12.47)	51	66
		24	13	07	—	—	4.38	2.28	1.23	—	—	7.9 (4.1-8.7)	2440 (970-2830)	11.17 (4.69-12.56)	51	66
		16	16	07	—	—	3.19	3.19	1.42	—	—	7.8 (4.1-8.6)	2430 (970-2810)	11.12 (4.69-12.47)	51	66
		18	16	07	—	—	3.39	3.05	1.36	—	—	7.8 (4.1-8.6)	2430 (970-2810)	11.12 (4.69-12.47)	51	66
		22	16	07	—	—	3.79	2.84	1.26	—	—	7.9 (4.1-8.7)	2440 (970-2830)	11.17 (4.69-12.56)	51	66
		24	16	07	—	—	4.12	2.61	1.16	—	—	7.9 (4.1-8.7)	2440 (970-2830)	11.17 (4.69-12.56)	51	66
		18	18	07	—	—	3.29	3.29	1.32	—	—	7.9 (4.1-8.7)	2440 (970-2830)	11.17 (4.69-12.56)	51	66
		22	18	07	—	—	3.65	3.04	1.22	—	—	7.9 (4.1-8.7)	2440 (970-2830)	11.17 (4.69-12.56)	51	66
		24	18	07	—	—	3.98	2.80	1.12	—	—	7.9 (4.1-8.7)	2440 (970-2830)	11.17 (4.69-12.56)	51	66
		10	10	10	—	—	2.53	2.53	2.53	—	—	7.6 (3.8-8.2)	2400 (950-2720)	10.98 (4.59-12.07)	51	66
		13	10	10	—	—	3.13	2.28	2.28	—	—	7.7 (3.9-8.3)	2410 (960-2740)	11.03 (4.64-12.16)	51	66
		16	10	10	—	—	3.50	2.10	2.10	—	—	7.7 (4.0-8.5)	2410 (960-2790)	11.03 (4.64-12.38)	51	66
		18	10	10	—	—	3.70	2.00	2.00	—	—	7.7 (4.0-8.5)	2410 (960-2790)	11.03 (4.64-12.38)	51	66
		22	10	10	—	—	4.16	1.87	1.87	—	—	7.9 (4.1-8.7)	2440 (970-2830)	11.17 (4.69-12.56)	51	66
		24	10	10	—	—	4.49	1.71	1.71	—	—	7.9 (4.1-8.7)	2440 (970-2830)	11.17 (4.69-12.56)	51	66
		13	13	10	—	—	2.82	2.82	2.06	—	—	7.7 (4.0-8.5)	2410 (960-2790)	11.03 (4.64-12.38)	51	66
		16	13	10	—	—	3.22	2.65	1.93	—	—	7.8 (4.1-8.6)	2430 (970-2810)	11.12 (4.69-12.47)	51	66
		18	13	10	—	—	3.42	2.53	1.85	—	—	7.8 (4.1-8.6)	2430 (970-2810)	11.12 (4.69-12.47)	51	66
		22	13	10	—	—	3.82	2.36	1.72	—	—	7.9 (4.1-8.7)	2440 (970-2830)	11.17 (4.69-12.56)	51	66
		24	13	10	—	—	4.15	2.17	1.58	—	—	7.9 (4.1-8.7)	2440 (970-2830)	11.17 (4.69-12.56)	51	66
		16	16	10	—	—	3.04	3.04	1.82	—	—	7.9 (4.1-8.7)	2440 (970-2830)	11.17 (4.69-12.56)	51	66
		18	16	10	—	—	3.20	2.88	1.73	—	—	7.8 (4.1-8.6)	2430 (970-2810)	11.12 (4.69-12.47)	51	66
		22	16	10	—	—	3.64	2.73	1.64	—	—	8.0 (4.3-9.0)	2450 (980-2900)	11.21 (4.73-12.87)	51	66
		24	16	10	—	—	3.97	2.52	1.51	—	—	8.0 (4.3-9.0)	2450 (980-2900)	11.21 (4.73-12.87)	51	66
18	18	10	—	—	3.11	3.11	1.68	—	—	7.9 (4.1-8.7)	2440 (970-2830)	11.17 (4.69-12.56)	51	66		
13	13	13	—	—												

<Cooling / 230V> (Continued)

Power supply (V)	Operating Status	Indoor unit					Unit Capacity					Total				Outdoor noise (dB)	
		A	B	C	D	E	A	B	C	D	E	Cooling capacity (kW)	Power consumption (W)	Operating current (A)	Sound Pressure	Sound Power	
230	4 units	07	07	07	07	—	2.00	2.00	2.00	2.00	—	8.0 (4.0-8.7)	2550 (930-2800)	11.67 (4.49-12.42)	51	66	
		10	07	07	07	—	2.61	1.93	1.93	1.93	—	8.4 (4.0-8.8)	2710 (930-2820)	12.40 (4.49-12.51)	51	66	
		13	07	07	07	—	3.28	1.77	1.77	1.77	—	8.6 (4.1-9.0)	2720 (940-2850)	12.45 (4.54-12.64)	51	66	
		16	07	07	07	—	3.73	1.66	1.66	1.66	—	8.7 (4.1-9.1)	2720 (940-2850)	12.45 (4.54-12.64)	51	66	
		18	07	07	07	—	4.00	1.60	1.60	1.60	—	8.8 (4.1-9.2)	2730 (940-2880)	12.49 (4.54-12.78)	51	66	
		22	07	07	07	—	4.45	1.48	1.48	1.48	—	8.9 (4.1-9.3)	2730 (940-2880)	12.49 (4.54-12.78)	51	66	
		24	07	07	07	—	4.88	1.37	1.37	1.37	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		10	10	07	07	—	2.44	2.44	1.81	1.81	—	8.5 (4.0-8.9)	2710 (930-2820)	12.40 (4.49-12.51)	51	66	
		13	10	07	07	—	3.10	2.26	1.67	1.67	—	8.7 (4.1-9.1)	2720 (940-2850)	12.45 (4.54-12.64)	51	66	
		16	10	07	07	—	3.54	2.12	1.57	1.57	—	8.8 (4.1-9.2)	2730 (940-2880)	12.49 (4.54-12.78)	51	66	
		18	10	07	07	—	3.80	2.05	1.52	1.52	—	8.8 (4.1-9.3)	2730 (940-2880)	12.49 (4.54-12.78)	51	66	
		22	10	07	07	—	4.25	1.91	1.42	1.42	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		24	10	07	07	—	4.63	1.76	1.30	1.30	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		13	13	07	07	—	2.89	2.89	1.56	1.56	—	8.9 (4.1-9.3)	2730 (940-2880)	12.49 (4.54-12.78)	51	66	
		16	13	07	07	—	3.32	2.73	1.48	1.48	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		18	13	07	07	—	3.54	2.62	1.42	1.42	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		22	13	07	07	—	3.94	2.43	1.31	1.31	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		24	13	07	07	—	4.32	2.25	1.22	1.22	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		16	16	07	07	—	3.12	3.12	1.38	1.38	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		18	16	07	07	—	3.33	3.00	1.33	1.33	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		22	16	07	07	—	3.72	2.79	1.24	1.24	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		24	16	07	07	—	4.10	2.60	1.15	1.15	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		18	18	07	07	—	3.21	3.21	1.29	1.29	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		22	18	07	07	—	3.60	3.00	1.20	1.20	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		24	18	07	07	—	3.97	2.80	1.12	1.12	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		10	10	10	07	—	2.30	2.30	2.30	1.70	—	8.6 (4.1-9.0)	2720 (940-2850)	12.45 (4.54-12.64)	51	66	
		13	10	10	07	—	2.93	2.14	2.14	1.59	—	8.8 (4.1-9.2)	2730 (940-2880)	12.49 (4.54-12.78)	51	66	
		16	10	10	07	—	3.37	2.02	2.02	1.50	—	8.9 (4.1-9.3)	2730 (940-2880)	12.49 (4.54-12.78)	51	66	
		18	10	10	07	—	3.63	1.96	1.96	1.45	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		22	10	10	07	—	4.03	1.81	1.81	1.34	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		24	10	10	07	—	4.41	1.68	1.68	1.24	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		13	13	10	07	—	2.75	2.75	2.01	1.49	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		16	13	10	07	—	3.14	2.58	1.88	1.40	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		18	13	10	07	—	3.36	2.49	1.81	1.34	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		22	13	10	07	—	3.75	2.31	1.69	1.25	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		24	13	10	07	—	4.12	2.15	1.57	1.16	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		16	16	10	07	—	2.96	2.96	1.77	1.31	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		18	16	10	07	—	3.17	2.85	1.71	1.27	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		22	16	10	07	—	3.55	2.66	1.60	1.18	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		24	16	10	07	—	3.92	2.48	1.49	1.10	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		18	18	10	07	—	3.06	3.06	1.65	1.22	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		22	18	10	07	—	3.44	2.87	1.55	1.15	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		24	18	10	07	—	3.80	2.68	1.45	1.07	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		13	13	13	07	—	2.54	2.54	2.54	1.37	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		16	13	13	07	—	2.91	2.40	2.40	1.29	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		18	13	13	07	—	3.13	2.31	2.31	1.25	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		22	13	13	07	—	3.51	2.16	2.16	1.17	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		24	13	13	07	—	3.87	2.02	2.02	1.09	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		16	16	13	07	—	2.76	2.76	2.27	1.22	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		18	16	13	07	—	2.96	2.66	2.19	1.18	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		22	16	13	07	—	3.33	2.50	2.06	1.11	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		24	16	13	07	—	3.69	2.34	1.92	1.04	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		18	18	13	07	—	2.87	2.87	2.12	1.15	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		22	18	13	07	—	3.23	2.69	1.99	1.08	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		24	18	13	07	—	3.59	2.53	1.87	1.01	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		10	10	10	10	—	2.18	2.18	2.18	2.18	—	8.7 (4.1-9.1)	2720 (940-2850)	12.45 (4.54-12.64)	51	66	
		13	10	10	10	—	2.79	2.04	2.04	2.04	—	8.9 (4.1-9.3)	2730 (940-2880)	12.49 (4.54-12.78)	51	66	
		16	10	10	10	—	3.21	1.93	1.93	1.93	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		18	10	10	10	—	3.44	1.85	1.85	1.85	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		22	10	10	10	—	3.83	1.72	1.72	1.72	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		24	10	10	10	—	4.20	1.60	1.60	1.60	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		13	13	10	10	—	2.60	2.60	1.90	1.90	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		16	13	10	10	—	2.98	2.45	1.79	1.79	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		22	13	10	10	—	3.58	2.21	1.61	1.61	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		24	13	10	10	—	3.94	2.06	1.50	1.50	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		16	16	10	10	—	2.81	2.81	1.69	1.69	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
		18	13	10	10	—	3.19	2.36	1.72	1.72	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66	
22	16	10	10	—	3.40	2.55	1.53	1.53	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66			
24	16	10	10	—	3.76	2.38	1.43	1.43	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66			
18	16	10	10	—	3.02	2.72	1.63	1.63	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66			
18	18	10	10	—	2.92	2.92	1.58	1.58	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66			
22	18	10	10	—	3.29	2.74	1.48	1.48	—	9.0 (4.2-9.4)	2740 (950-2900)	12.54 (4.59-12.87)	51	66			
24	18	10	10	—	3.65	2.57	1.39	1.39	—	9.0 (4							

<Cooling / 230V> (Continued)

Power supply (V)	Operating Status	Indoor unit					Unit Capacity					Total			Outdoor noise (dB)	
		A	B	C	D	E	A	B	C	D	E	Cooling capacity (kW)	Power consumption (W)	Operating current (A)	Sound Pressure	Sound Power
230	5 units	07	07	07	07	07	1.96	1.96	1.96	1.96	1.96	9.8 (3.7-10.8)	2865 (950-3630)	13.11 (4.59-16.10)	51	66
		10	07	07	07	07	2.50	1.85	1.85	1.85	1.85	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		13	07	07	07	07	3.13	1.69	1.69	1.69	1.69	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		16	07	07	07	07	3.56	1.58	1.58	1.58	1.58	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		18	07	07	07	07	3.81	1.52	1.52	1.52	1.52	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		10	10	07	07	07	2.34	2.34	1.74	1.74	1.74	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		13	10	07	07	07	2.95	2.16	1.60	1.60	1.60	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		16	10	07	07	07	3.38	2.03	1.50	1.50	1.50	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		18	10	07	07	07	3.61	1.95	1.45	1.45	1.45	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		13	13	07	07	07	2.73	2.73	1.48	1.48	1.48	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		16	13	07	07	07	3.14	2.58	1.39	1.39	1.39	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		18	13	07	07	07	3.37	2.49	1.35	1.35	1.35	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		16	16	07	07	07	2.97	2.97	1.32	1.32	1.32	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		18	16	07	07	07	3.19	2.87	1.28	1.28	1.28	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		10	10	10	07	07	2.21	2.21	2.21	1.64	1.64	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		13	10	10	07	07	2.80	2.04	2.04	1.51	1.51	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		13	13	10	07	07	2.60	2.60	1.90	1.40	1.40	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		16	10	10	07	07	3.21	1.92	1.92	1.42	1.42	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		18	10	10	07	07	3.44	1.86	1.86	1.38	1.38	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		13	13	13	07	07	2.43	2.43	2.43	1.31	1.31	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		16	13	13	07	07	2.80	2.30	2.30	1.25	1.25	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		18	13	13	07	07	3.02	2.23	2.23	1.21	1.21	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		16	16	10	07	07	2.84	2.84	1.70	1.26	1.26	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		18	16	10	07	07	3.06	2.75	1.65	1.22	1.22	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		16	16	13	07	07	2.67	2.67	2.19	1.19	1.19	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		18	16	13	07	07	2.88	2.59	2.13	1.15	1.15	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		10	10	10	10	07	2.09	2.09	2.09	2.09	1.55	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		13	10	10	10	07	2.65	1.94	1.94	1.94	1.43	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		16	10	10	10	07	3.05	1.83	1.83	1.83	1.36	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		18	10	10	10	07	3.28	1.77	1.77	1.77	1.31	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		13	13	10	10	07	2.48	2.48	1.81	1.81	1.34	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		16	13	10	10	07	2.86	2.35	1.71	1.71	1.27	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		18	13	10	10	07	3.07	2.28	1.66	1.66	1.23	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		16	16	10	10	07	2.72	2.72	1.63	1.63	1.21	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		13	13	13	10	07	2.32	2.32	2.32	1.69	1.25	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		16	13	13	10	07	2.68	2.21	2.21	1.61	1.19	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		16	16	13	10	07	2.56	2.56	2.11	1.54	1.14	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		13	13	13	13	07	2.18	2.18	2.18	2.18	1.18	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		16	13	13	13	07	2.53	2.08	2.08	2.08	1.13	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		16	16	13	13	07	2.42	2.42	1.99	1.99	1.08	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		10	10	10	10	10	1.98	1.98	1.98	1.98	1.98	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		13	10	10	10	10	2.53	1.84	1.84	1.84	1.84	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		16	10	10	10	10	2.91	1.75	1.75	1.75	1.75	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		18	10	10	10	10	3.13	1.69	1.69	1.69	1.69	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		13	13	10	10	10	2.36	2.36	1.72	1.72	1.72	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		16	13	10	10	10	2.73	2.25	1.64	1.64	1.64	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		18	13	10	10	10	2.95	2.18	1.59	1.59	1.59	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		16	16	10	10	10	2.61	2.61	1.56	1.56	1.56	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		13	13	13	10	10	2.22	2.22	2.22	1.62	1.62	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		16	13	13	10	10	2.58	2.12	2.12	1.55	1.55	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		18	13	13	10	10	2.78	2.06	2.06	1.50	1.50	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		16	16	13	10	10	2.49	2.49	2.04	1.49	1.49	10.0 (3.7-11.0)	2923 (950-3700)	13.38 (4.59-16.42)	51	66
		13	13	13	13	10	2.09	2.09	2.09	2.09	1.53	9.9 (3.7-10.9)	2894 (950-3670)	13.24 (4.59-16.28)	51	66
		16	13	13	13	10	2.46	2.02	2.02	2.02	1.48	10.0 (3.7-11.0)	2923 (950-3700)	13.38 (4.59-16.42)	51	66
		18	13	13	13	10	2.66	1.97	1.97	1.97	1.44	10.0 (3.7-11.0)	2923 (950-3700)	13.38 (4.59-16.42)	51	66
		16	16	13	13	10	2.36	2.36	1.94	1.94	1.41	10.0 (3.7-11.0)	2923 (950-3700)	13.38 (4.59-16.42)	51	66
		13	13	13	13	13	2.00	2.00	2.00	2.00	2.00	10.0 (3.7-11.0)	2923 (950-3700)	13.38 (4.59-16.42)	51	66
		16	13	13	13	13	2.33	1.92	1.92	1.92	1.92	10.0 (3.7-11.0)	2923 (950-3700)	13.38 (4.59-16.42)	51	66
		22	07*	07*	07*	07*	4.29	1.43	1.43	1.43	1.43	10.0 (3.7-11.0)	2923 (950-3700)	13.38 (4.59-16.42)	51	66
		22	10*	07*	07*	07*	4.08	1.84	1.36	1.36	1.36	10.0 (3.7-11.0)	2923 (950-3700)	13.38 (4.59-16.42)	51	66
		22	10*	10*	07*	07*	3.90	1.75	1.75	1.30	1.30	10.0 (3.7-11.0)	2923 (950-3700)	13.38 (4.59-16.42)	51	66
		22	10*	10*	10*	07*	3.73	1.68	1.68	1.68	1.24	10.0 (3.7-11.0)	2923 (950-3700)	13.38 (4.59-16.42)	51	66
		22	10*	10*	10*	10*	3.57	1.61	1.61	1.61	1.61	10.0 (3.7-11.0)	2923 (950-3700)	13.38 (4.59-16.42)	51	66
		22	13*	07*	07*	07*	3.82	2.36	1.27	1.27	1.27	10.0 (3.7-11.0)	2923 (950-3700)	13.38 (4.59-16.42)	51	66
		22	13*	10*	07*	07*	3.66	2.26	1.65	1.22	1.22	10.0 (3.7-11.0)	2923 (950-3700)	13.38 (4.59-16.42)	51	66
		22	13*	10*	10*	07*	3.51	2.16	1.58	1.58	1.17	10.0 (3.7-11.0)	2923 (950-3700)	13.38 (4.59-16.42)	51	66
		22	13*	10*	10*	10*	3.37	2.08	1.52	1.52	1.52	10.0 (3.7-11.0)	2923 (950-3700)	13.38 (4.59-16.42)	51	66
		22	13*	13*	07*	07*	3.45	2.13	2.13	1.15	1.15	10.0 (3.7-11.0)	2923 (950-3700)	13.38 (4.59-16.42)	51	66
		22	13*	13*	10*	07*	3.31	2.04	2.04	1.49	1.10	10.0 (3.7-11.0)	2923 (950-3700)	13.38 (4.59-16.42)	51	66
		22	13*	13*	10*	10*	3.19	1.97	1.97	1.44	1.44	10.0 (3.7-11.0)	2923 (950-3700)	13.38 (4.59-16.42)	51	66
22	13*	13*	13*	07*	3.14	1.94	1.94	1.94	1.05	10.0 (3.7-11.0)	2923 (950-3700)	13.38 (4.59-16.42)	51	66		
24	07*	07*	07*	07*	4.70	1.32	1.32	1.32	1.32	10.0 (3.7-11.0)	2923 (950-3700)	13.38 (4.59-16.42)	51	66		
24	10*	07*	07*	07*	4.49	1.71	1.27	1.27	1.27							

<Cooling / 240V>

Power supply (V)	Operating Status	Indoor unit					Unit Capacity					Total			Outdoor noise (dB)	
		A	B	C	D	E	A	B	C	D	E	Cooling capacity (kW)	Power consumption (W)	Operating current (A)	Sound Pressure	Sound Power
240	1 unit	07	—	—	—	—	2.0	—	—	—	—	2.0 (1.4-2.5)	650 (640-700)	3.52 (3.51-3.43)	51	66
		10	—	—	—	—	2.7	—	—	—	—	2.7 (1.4-3.2)	750 (640-950)	4.06 (3.51-4.26)	51	66
		13	—	—	—	—	3.7	—	—	—	—	3.7 (1.4-4.4)	1200 (640-1520)	5.68 (3.38-6.60)	51	66
		16	—	—	—	—	4.5	—	—	—	—	4.5 (1.4-5.0)	1650 (640-2000)	7.31 (3.38-8.50)	51	66
		18	—	—	—	—	5.0	—	—	—	—	5.0 (1.4-5.2)	1950 (640-2100)	8.55 (3.38-8.93)	51	66
		22	—	—	—	—	6.0	—	—	—	—	6.0 (2.4-6.8)	2020 (640-2500)	8.77 (3.38-10.63)	51	66
		24	—	—	—	—	7.1	—	—	—	—	7.1 (2.4-7.2)	2390 (660-2960)	10.37 (3.48-12.59)	51	66
	2 units	07	07	—	—	—	2.00	2.00	—	—	—	4.0 (2.5-5.0)	1520 (640-1770)	6.67 (3.33-7.53)	51	66
		10	07	—	—	—	2.70	2.00	—	—	—	4.7 (2.5-5.7)	1530 (640-1910)	6.71 (3.33-8.12)	51	66
		13	07	—	—	—	3.70	2.00	—	—	—	5.7 (2.6-6.5)	1810 (660-2130)	7.94 (3.44-9.06)	51	66
		16	07	—	—	—	4.08	1.82	—	—	—	5.9 (2.7-6.6)	1810 (660-2220)	7.94 (3.44-9.44)	51	66
		18	07	—	—	—	4.50	1.80	—	—	—	6.3 (2.9-6.9)	2040 (670-2400)	8.95 (3.49-10.20)	51	66
		22	07	—	—	—	4.73	1.58	—	—	—	6.3 (2.9-6.9)	2040 (670-2400)	8.95 (3.49-10.20)	51	66
		24	07	—	—	—	5.31	1.49	—	—	—	6.8 (3.0-7.2)	2320 (690-2570)	10.18 (3.59-10.93)	51	66
		10	10	—	—	—	2.70	2.70	—	—	—	5.4 (2.5-6.3)	1530 (640-2040)	6.71 (3.33-8.67)	51	66
		13	10	—	—	—	3.41	2.49	—	—	—	5.9 (2.7-6.6)	1810 (660-2220)	7.94 (3.44-9.44)	51	66
		16	10	—	—	—	3.94	2.36	—	—	—	6.3 (2.9-6.9)	2040 (670-2400)	8.95 (3.49-10.20)	51	66
		18	10	—	—	—	4.09	2.21	—	—	—	6.3 (2.9-6.9)	2040 (670-2400)	8.95 (3.49-10.20)	51	66
		22	10	—	—	—	4.69	2.11	—	—	—	6.8 (3.0-7.2)	2320 (690-2570)	10.18 (3.59-10.93)	51	66
		24	10	—	—	—	5.22	1.98	—	—	—	7.2 (3.2-7.5)	2550 (700-2750)	11.18 (3.65-11.69)	51	66
		13	13	—	—	—	3.15	3.15	—	—	—	6.3 (2.9-6.9)	2040 (670-2400)	8.95 (3.49-10.20)	51	66
		16	13	—	—	—	3.73	3.07	—	—	—	6.8 (3.0-7.2)	2320 (690-2570)	10.18 (3.59-10.93)	51	66
		18	13	—	—	—	3.91	2.89	—	—	—	6.8 (3.0-7.2)	2320 (690-2570)	10.18 (3.59-10.93)	51	66
		22	13	—	—	—	4.45	2.75	—	—	—	7.2 (3.2-7.5)	2550 (700-2750)	11.18 (3.65-11.69)	51	66
		24	13	—	—	—	4.73	2.47	—	—	—	7.2 (3.2-7.5)	2550 (700-2750)	11.18 (3.65-11.69)	51	66
		16	16	—	—	—	3.60	3.60	—	—	—	7.2 (3.2-7.5)	2550 (700-2750)	11.18 (3.65-11.69)	51	66
		18	16	—	—	—	3.79	3.41	—	—	—	7.2 (3.2-7.5)	2550 (700-2750)	11.18 (3.65-11.69)	51	66
		22	16	—	—	—	4.17	3.13	—	—	—	7.3 (3.2-7.5)	2550 (700-2750)	11.18 (3.65-11.69)	51	66
		24	16	—	—	—	4.47	2.83	—	—	—	7.3 (3.2-7.5)	2550 (700-2750)	11.18 (3.65-11.69)	51	66
		18	18	—	—	—	3.60	3.60	—	—	—	7.2 (3.2-7.5)	2550 (700-2750)	11.18 (3.65-11.69)	51	66
		22	18	—	—	—	4.04	3.36	—	—	—	7.4 (3.2-7.5)	2550 (700-2750)	11.18 (3.65-11.69)	51	66
		24	18	—	—	—	4.34	3.06	—	—	—	7.4 (3.2-7.5)	2550 (700-2750)	11.18 (3.65-11.69)	51	66
		22	22	—	—	—	4.00	4.00	—	—	—	8.0 (3.2-8.3)	2170 (700-2370)	9.42 (3.65-10.08)	51	66
		22	24	—	—	—	3.66	4.34	—	—	—	8.0 (3.2-8.3)	2170 (700-2370)	9.42 (3.65-10.08)	51	66
		24	24	—	—	—	4.05	4.05	—	—	—	8.1 (3.2-8.4)	2200 (700-2400)	9.55 (3.65-10.20)	51	66
	3 units	07	07	07	—	—	2.00	2.00	2.00	—	—	6.0 (3.8-7.5)	2400 (950-2720)	10.53 (4.40-11.56)	51	66
		10	07	07	—	—	2.70	2.00	2.00	—	—	6.7 (3.8-8.2)	2400 (950-2720)	10.53 (4.40-11.56)	51	66
		13	07	07	—	—	3.65	1.97	1.97	—	—	7.6 (3.9-8.3)	2410 (960-2740)	10.57 (4.44-11.65)	51	66
		16	07	07	—	—	4.08	1.81	1.81	—	—	7.7 (4.0-8.5)	2410 (960-2790)	10.57 (4.44-11.86)	51	66
		18	07	07	—	—	4.28	1.71	1.71	—	—	7.7 (4.0-8.5)	2410 (960-2790)	10.57 (4.44-11.86)	51	66
		22	07	07	—	—	4.68	1.56	1.56	—	—	7.8 (4.1-8.6)	2430 (970-2810)	10.66 (4.49-11.95)	51	66
		24	07	07	—	—	4.99	1.41	1.41	—	—	7.8 (4.1-8.6)	2430 (970-2810)	10.66 (4.49-11.95)	51	66
		10	10	07	—	—	2.70	2.70	2.00	—	—	7.4 (3.8-8.2)	2400 (950-2720)	10.53 (4.40-11.56)	51	66
		13	10	07	—	—	3.39	2.48	1.83	—	—	7.7 (3.9-8.3)	2410 (960-2740)	10.57 (4.44-11.65)	51	66
		16	10	07	—	—	3.77	2.26	1.67	—	—	7.7 (4.0-8.5)	2410 (960-2790)	10.57 (4.44-11.86)	51	66
		18	10	07	—	—	3.97	2.14	1.59	—	—	7.7 (4.0-8.5)	2410 (960-2790)	10.57 (4.44-11.86)	51	66
		22	10	07	—	—	4.37	1.97	1.46	—	—	7.8 (4.1-8.6)	2430 (970-2810)	10.66 (4.49-11.95)	51	66
		24	10	07	—	—	4.69	1.78	1.32	—	—	7.8 (4.1-8.6)	2430 (970-2810)	10.66 (4.49-11.95)	51	66
		13	13	07	—	—	3.03	3.03	1.64	—	—	7.7 (4.0-8.5)	2410 (960-2790)	10.57 (4.44-11.86)	51	66
		16	13	07	—	—	3.44	2.83	1.53	—	—	7.8 (4.1-8.6)	2430 (970-2810)	10.66 (4.49-11.95)	51	66
		18	13	07	—	—	3.64	2.70	1.46	—	—	7.8 (4.1-8.6)	2430 (970-2810)	10.66 (4.49-11.95)	51	66
		22	13	07	—	—	4.00	2.47	1.33	—	—	7.8 (4.1-8.6)	2430 (970-2810)	10.66 (4.49-11.95)	51	66
		24	13	07	—	—	4.38	2.28	1.23	—	—	7.9 (4.1-8.7)	2440 (970-2830)	10.70 (4.49-12.03)	51	66
		16	16	07	—	—	3.19	3.19	1.42	—	—	7.8 (4.1-8.6)	2430 (970-2810)	10.66 (4.49-11.95)	51	66
		18	16	07	—	—	3.39	3.05	1.36	—	—	7.8 (4.1-8.6)	2430 (970-2810)	10.66 (4.49-11.95)	51	66
		22	16	07	—	—	3.79	2.84	1.26	—	—	7.9 (4.1-8.7)	2440 (970-2830)	10.70 (4.49-12.03)	51	66
		24	16	07	—	—	4.12	2.61	1.16	—	—	7.9 (4.1-8.7)	2440 (970-2830)	10.70 (4.49-12.03)	51	66
		18	18	07	—	—	3.29	3.29	1.32	—	—	7.9 (4.1-8.7)	2440 (970-2830)	10.70 (4.49-12.03)	51	66
		22	18	07	—	—	3.65	3.04	1.22	—	—	7.9 (4.1-8.7)	2440 (970-2830)	10.70 (4.49-12.03)	51	66
		24	18	07	—	—	3.98	2.80	1.12	—	—	7.9 (4.1-8.7)	2440 (970-2830)	10.70 (4.49-12.03)	51	66
		10	10	10	—	—	2.53	2.53	2.53	—	—	7.6 (3.8-8.2)	2400 (950-2720)	10.53 (4.40-11.56)	51	66
		13	10	10	—	—	3.13	2.28	2.28	—	—	7.7 (3.9-8.3)	2410 (960-2740)	10.57 (4.44-11.65)	51	66
		16	10	10	—	—	3.50	2.10	2.10	—	—	7.7 (4.0-8.5)	2410 (960-2790)	10.57 (4.44-11.86)	51	66
		18	10	10	—	—	3.70	2.00	2.00	—	—	7.7 (4.0-8.5)	2410 (960-2790)	10.57 (4.44-11.86)	51	66
		22	10	10	—	—	4.16	1.87	1.87	—	—	7.9 (4.1-8.7)	2440 (970-2830)	10.70 (4.49-12.03)	51	66
		24	10	10	—	—	4.49	1.71	1.71	—	—	7.9 (4.1-8.7)	2440 (970-2830)	10.70 (4.49-12.03)	51	66
		13	13	10	—	—	2.82	2.82	2.06	—	—	7.7 (4.0-8.5)	2410 (960-2790)	10.57 (4.44-11.86)	51	66
		16	13	10	—	—	3.22	2.65	1.93	—	—	7.8 (4.1-8.6)	2430 (970-2810)	10.66 (4.49-11.95)	51	66
		18	13	10	—	—	3.42	2.53	1.85	—	—	7.8 (4.1-8.6)	2430 (970-2810)	10.66 (4.49-11.95)	51	66
		22	13	10	—	—	3.82	2.36	1.72	—	—	7.9 (4.1-8.7)	2440 (970-2830)	10.70 (4.49-12.03)	51	66
		24	13	10	—	—	4.15	2.17	1.58	—	—	7.9 (4.1-8.7)	2440 (970-2830)	10.70 (4.49-12.03)	51	66
		16	16	10	—	—	3.04	3.04	1.82	—	—	7.9 (4.1-8.7)	2440 (970-2830)	10.70 (4.49-12.03)	51	66
		18	16	10	—	—	3.20	2.88	1.73	—	—	7.8 (4.1-8.6)	2430 (970-2810)	10.66 (4.49-11.95)	51	66
		22	16	10	—	—	3.64	2.73	1.64	—	—	8.0 (4.3-9.0)	2450 (980-2900)	10.75 (4.54-12.33)	51	66
		24	16	10	—	—	3.97	2.52	1.51	—	—	8.0 (4.3-9.0)	2450 (980-2900)	10.75 (4.54-12.33)	51	66
18	18	10	—	—	3.11	3.11	1.68	—	—	7.9 (4.1-8.7)	2440 (970-2830)	10.70 (4.49-12.03)	51	66		
13	13	13	—	—	2.60											

<Cooling / 240V> (Continued)

Power supply (V)	Operating Status	Indoor unit					Unit Capacity					Total				Outdoor noise (dB)	
		A	B	C	D	E	A	B	C	D	E	Cooling capacity (kW)	Power consumption (W)	Operating current (A)	Sound Pressure	Sound Power	
240	4 units	07	07	07	07	—	2.00	2.00	2.00	2.00	—	8.0 (4.0-8.7)	2550 (930-2800)	11.18 (4.31-11.90)	51	66	
		10	07	07	07	—	2.61	1.93	1.93	1.93	—	8.4 (4.0-8.8)	2710 (930-2820)	11.89 (4.31-11.99)	51	66	
		13	07	07	07	—	3.28	1.77	1.77	1.77	—	8.6 (4.1-9.0)	2720 (940-2850)	11.93 (4.35-12.12)	51	66	
		16	07	07	07	—	3.73	1.66	1.66	1.66	—	8.7 (4.1-9.1)	2720 (940-2850)	11.93 (4.35-12.12)	51	66	
		18	07	07	07	—	4.00	1.60	1.60	1.60	—	8.8 (4.1-9.2)	2730 (940-2880)	11.97 (4.35-12.24)	51	66	
		22	07	07	07	—	4.45	1.48	1.48	1.48	—	8.9 (4.1-9.3)	2730 (940-2880)	11.97 (4.35-12.24)	51	66	
		24	07	07	07	—	4.88	1.37	1.37	1.37	—	9.0 (4.1-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		10	10	07	07	—	2.44	2.44	1.81	1.81	—	8.5 (4.0-8.9)	2710 (930-2820)	11.89 (4.31-11.99)	51	66	
		13	10	07	07	—	3.10	2.26	1.67	1.67	—	8.7 (4.1-9.1)	2720 (940-2850)	11.93 (4.35-12.12)	51	66	
		16	10	07	07	—	3.54	2.12	1.57	1.57	—	8.8 (4.1-9.2)	2730 (940-2880)	11.97 (4.35-12.24)	51	66	
		18	10	07	07	—	3.80	2.05	1.52	1.52	—	8.9 (4.1-9.3)	2730 (940-2880)	11.97 (4.35-12.24)	51	66	
		22	10	07	07	—	4.25	1.91	1.42	1.42	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		24	10	07	07	—	4.63	1.76	1.30	1.30	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		13	13	07	07	—	2.89	2.89	1.56	1.56	—	8.9 (4.1-9.3)	2730 (940-2880)	11.97 (4.35-12.24)	51	66	
		16	13	07	07	—	3.32	2.73	1.48	1.48	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		18	13	07	07	—	3.54	2.62	1.42	1.42	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		22	13	07	07	—	3.94	2.43	1.31	1.31	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		24	13	07	07	—	4.32	2.25	1.22	1.22	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		16	16	07	07	—	3.12	3.12	1.38	1.38	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		18	16	07	07	—	3.33	3.00	1.33	1.33	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		22	16	07	07	—	3.72	2.79	1.24	1.24	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		24	16	07	07	—	4.10	2.60	1.15	1.15	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		18	18	07	07	—	3.21	3.21	1.29	1.29	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		22	18	07	07	—	3.60	3.00	1.20	1.20	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		24	18	07	07	—	3.97	2.80	1.12	1.12	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		10	10	10	07	—	2.30	2.30	2.30	1.70	—	8.6 (4.1-9.0)	2720 (940-2850)	11.93 (4.35-12.12)	51	66	
		13	10	10	07	—	2.93	2.14	2.14	1.59	—	8.8 (4.1-9.2)	2730 (940-2880)	11.97 (4.35-12.24)	51	66	
		16	10	10	07	—	3.37	2.02	2.02	1.50	—	8.9 (4.1-9.3)	2730 (940-2880)	11.97 (4.35-12.24)	51	66	
		18	10	10	07	—	3.63	1.96	1.96	1.45	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		22	10	10	07	—	4.03	1.81	1.81	1.34	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		24	10	10	07	—	4.41	1.68	1.68	1.24	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		13	13	10	07	—	2.75	2.75	2.01	1.49	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		16	13	10	07	—	3.14	2.58	1.88	1.40	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		18	13	10	07	—	3.36	2.49	1.81	1.34	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		22	13	10	07	—	3.75	2.31	1.69	1.25	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		24	13	10	07	—	4.12	2.15	1.57	1.16	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		16	16	10	07	—	2.96	2.96	1.77	1.31	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		18	16	10	07	—	3.17	2.85	1.71	1.27	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		22	16	10	07	—	3.55	2.66	1.60	1.18	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		24	16	10	07	—	3.92	2.48	1.49	1.10	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		18	18	10	07	—	3.06	3.06	1.65	1.22	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		22	18	10	07	—	3.44	2.87	1.55	1.15	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		24	18	10	07	—	3.80	2.68	1.45	1.07	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		13	13	13	07	—	2.54	2.54	2.54	1.37	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		16	13	13	07	—	2.91	2.40	2.40	1.29	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		18	13	13	07	—	3.13	2.31	2.31	1.25	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		22	13	13	07	—	3.51	2.16	2.16	1.17	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		24	13	13	07	—	3.87	2.02	2.02	1.09	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		16	16	13	07	—	2.76	2.76	2.27	1.22	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		18	16	13	07	—	2.96	2.66	2.19	1.18	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		22	16	13	07	—	3.33	2.50	2.06	1.11	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		24	16	13	07	—	3.69	2.34	1.92	1.04	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		18	18	13	07	—	2.87	2.87	2.12	1.15	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		22	18	13	07	—	3.23	2.69	1.99	1.08	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		24	18	13	07	—	3.59	2.53	1.87	1.01	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		10	10	10	10	—	2.18	2.18	2.18	2.18	—	8.7 (4.1-9.1)	2720 (940-2850)	11.93 (4.35-12.12)	51	66	
		13	10	10	10	—	2.79	2.04	2.04	2.04	—	8.9 (4.1-9.3)	2730 (940-2880)	11.97 (4.35-12.24)	51	66	
		16	10	10	10	—	3.21	1.93	1.93	1.93	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		18	10	10	10	—	3.44	1.85	1.85	1.85	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		22	10	10	10	—	3.83	1.72	1.72	1.72	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		24	10	10	10	—	4.20	1.60	1.60	1.60	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		13	13	10	10	—	2.60	2.60	1.90	1.90	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		16	13	10	10	—	2.98	2.45	1.79	1.79	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		22	13	10	10	—	3.58	2.21	1.61	1.61	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		24	13	10	10	—	3.94	2.06	1.50	1.50	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		16	16	10	10	—	2.81	2.81	1.69	1.69	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		18	13	10	10	—	3.19	2.36	1.72	1.72	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
		22	16	10	10	—	3.40	2.55	1.53	1.53	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66	
24	16	10	10	—	3.76	2.38	1.43	1.43	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66			
18	16	10	10	—	3.02	2.72	1.63	1.63	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66			
18	18	10	10	—	2.92	2.92	1.58	1.58	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66			
22	18	10	10	—	3.29	2.74	1.48	1.48	—	9.0 (4.2-9.4)	2740 (950-2900)	12.02 (4.40-12.33)	51	66			
24	18	10	10	—													

<Cooling / 240V> (Continued)

Power supply (V)	Operating Status	Indoor unit					Unit Capacity					Total			Outdoor noise (dB)	
		A	B	C	D	E	A	B	C	D	E	Cooling capacity (kW)	Power consumption (W)	Operating current (A)	Sound Pressure	Sound Power
240	5 units	07 07 07 07 07	1.96	1.96	1.96	1.96	1.96	1.96	1.96	1.96	1.96	9.8 (3.7-10.8)	2865 (950-3630)	12.57 (4.40-15.43)	51	66
		10 07 07 07 07	2.50	1.85	1.85	1.85	1.85	1.85	1.85	1.85	1.85	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		13 07 07 07 07	3.13	1.69	1.69	1.69	1.69	1.69	1.69	1.69	1.69	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		16 07 07 07 07	3.56	1.58	1.58	1.58	1.58	1.58	1.58	1.58	1.58	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		18 07 07 07 07	3.81	1.52	1.52	1.52	1.52	1.52	1.52	1.52	1.52	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		10 10 07 07 07	2.34	2.34	1.74	1.74	1.74	1.74	1.74	1.74	1.74	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		13 10 07 07 07	2.95	2.16	1.60	1.60	1.60	1.60	1.60	1.60	1.60	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		16 10 07 07 07	3.38	2.03	1.50	1.50	1.50	1.50	1.50	1.50	1.50	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		18 10 07 07 07	3.61	1.95	1.45	1.45	1.45	1.45	1.45	1.45	1.45	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		13 13 07 07 07	2.73	2.73	1.48	1.48	1.48	1.48	1.48	1.48	1.48	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		16 13 07 07 07	3.14	2.58	1.39	1.39	1.39	1.39	1.39	1.39	1.39	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		18 13 07 07 07	3.37	2.49	1.35	1.35	1.35	1.35	1.35	1.35	1.35	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		16 16 07 07 07	2.97	2.97	1.32	1.32	1.32	1.32	1.32	1.32	1.32	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		18 16 07 07 07	3.19	2.87	1.28	1.28	1.28	1.28	1.28	1.28	1.28	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		10 10 10 07 07	2.21	2.21	2.21	1.64	1.64	1.64	1.64	1.64	1.64	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		13 10 10 07 07	2.80	2.04	2.04	1.51	1.51	1.51	1.51	1.51	1.51	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		16 10 10 07 07	2.60	2.60	1.90	1.40	1.40	1.40	1.40	1.40	1.40	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		18 10 10 07 07	3.21	1.92	1.92	1.42	1.42	1.42	1.42	1.42	1.42	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		10 10 10 07 07	3.44	1.86	1.86	1.38	1.38	1.38	1.38	1.38	1.38	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		13 13 13 07 07	2.43	2.43	2.43	1.31	1.31	1.31	1.31	1.31	1.31	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		16 13 13 07 07	2.80	2.30	2.30	1.25	1.25	1.25	1.25	1.25	1.25	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		18 13 13 07 07	3.02	2.23	2.23	1.21	1.21	1.21	1.21	1.21	1.21	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		16 16 10 07 07	2.84	2.84	1.70	1.26	1.26	1.26	1.26	1.26	1.26	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		18 16 10 07 07	3.06	2.75	1.65	1.22	1.22	1.22	1.22	1.22	1.22	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		16 16 13 07 07	2.67	2.67	2.19	1.19	1.19	1.19	1.19	1.19	1.19	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		18 16 13 07 07	2.88	2.59	2.13	1.15	1.15	1.15	1.15	1.15	1.15	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		10 10 10 10 07	2.09	2.09	2.09	2.09	1.55	1.55	1.55	1.55	1.55	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		13 10 10 10 07	2.65	1.94	1.94	1.94	1.43	1.43	1.43	1.43	1.43	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		16 10 10 10 07	3.05	1.83	1.83	1.83	1.36	1.36	1.36	1.36	1.36	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		18 10 10 10 07	3.28	1.77	1.77	1.77	1.31	1.31	1.31	1.31	1.31	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		13 13 10 10 07	2.48	2.48	1.81	1.81	1.34	1.34	1.34	1.34	1.34	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		16 13 10 10 07	2.86	2.35	1.71	1.71	1.27	1.27	1.27	1.27	1.27	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		18 13 10 10 07	3.07	2.28	1.66	1.66	1.23	1.23	1.23	1.23	1.23	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		16 16 10 10 07	2.72	2.72	1.63	1.63	1.21	1.21	1.21	1.21	1.21	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		13 13 13 10 07	2.32	2.32	2.32	1.69	1.25	1.25	1.25	1.25	1.25	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		16 13 13 10 07	2.68	2.21	2.21	1.61	1.19	1.19	1.19	1.19	1.19	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		18 16 13 10 07	2.56	2.56	2.11	1.54	1.14	1.14	1.14	1.14	1.14	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		13 13 13 13 07	2.18	2.18	2.18	2.18	1.18	1.18	1.18	1.18	1.18	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		16 13 13 13 07	2.53	2.08	2.08	2.08	1.13	1.13	1.13	1.13	1.13	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		18 16 13 13 07	2.42	2.42	1.99	1.99	1.08	1.08	1.08	1.08	1.08	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		10 10 10 10 10	1.98	1.98	1.98	1.98	1.98	1.98	1.98	1.98	1.98	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		13 10 10 10 10	2.53	1.84	1.84	1.84	1.84	1.84	1.84	1.84	1.84	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		16 10 10 10 10	2.91	1.75	1.75	1.75	1.75	1.75	1.75	1.75	1.75	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		18 10 10 10 10	3.13	1.69	1.69	1.69	1.69	1.69	1.69	1.69	1.69	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		13 13 10 10 10	2.36	2.36	1.72	1.72	1.72	1.72	1.72	1.72	1.72	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		16 13 10 10 10	2.73	2.25	1.64	1.64	1.64	1.64	1.64	1.64	1.64	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		18 13 10 10 10	2.95	2.18	1.59	1.59	1.59	1.59	1.59	1.59	1.59	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		16 16 10 10 10	2.61	2.61	1.56	1.56	1.56	1.56	1.56	1.56	1.56	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		13 13 13 10 10	2.22	2.22	2.22	1.62	1.62	1.62	1.62	1.62	1.62	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		16 13 13 10 10	2.58	2.12	2.12	1.55	1.55	1.55	1.55	1.55	1.55	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		18 13 13 10 10	2.78	2.06	2.06	1.50	1.50	1.50	1.50	1.50	1.50	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		16 16 13 10 10	2.49	2.49	2.04	1.49	1.49	1.49	1.49	1.49	1.49	10.0 (3.7-11.0)	2923 (950-3700)	12.82 (4.40-15.73)	51	66
		13 13 13 13 10	2.09	2.09	2.09	2.09	1.53	1.53	1.53	1.53	1.53	9.9 (3.7-10.9)	2894 (950-3670)	12.69 (4.40-15.60)	51	66
		16 13 13 13 10	2.46	2.02	2.02	2.02	1.48	1.48	1.48	1.48	1.48	10.0 (3.7-11.0)	2923 (950-3700)	12.82 (4.40-15.73)	51	66
		18 13 13 13 10	2.66	1.97	1.97	1.97	1.44	1.44	1.44	1.44	1.44	10.0 (3.7-11.0)	2923 (950-3700)	12.82 (4.40-15.73)	51	66
		16 16 13 13 10	2.36	2.36	1.94	1.94	1.41	1.41	1.41	1.41	1.41	10.0 (3.7-11.0)	2923 (950-3700)	12.82 (4.40-15.73)	51	66
		13 13 13 13 13	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	2.00	10.0 (3.7-11.0)	2923 (950-3700)	12.82 (4.40-15.73)	51	66
		16 13 13 13 13	2.33	1.92	1.92	1.92	1.92	1.92	1.92	1.92	1.92	10.0 (3.7-11.0)	2923 (950-3700)	12.82 (4.40-15.73)	51	66
		22 07* 07* 07* 07*	4.29	1.43	1.43	1.43	1.43	1.43	1.43	1.43	1.43	10.0 (3.7-11.0)	2923 (950-3700)	12.82 (4.40-15.73)	51	66
		22 10* 07* 07* 07*	4.08	1.84	1.36	1.36	1.36	1.36	1.36	1.36	1.36	10.0 (3.7-11.0)	2923 (950-3700)	12.82 (4.40-15.73)	51	66
		22 10* 10* 07* 07*	3.90	1.75	1.75	1.30	1.30	1.30	1.30	1.30	1.30	10.0 (3.7-11.0)	2923 (950-3700)	12.82 (4.40-15.73)	51	66

Outdoor Unit : RAS-5M34UAV-E1
<Heating / 220V>

Power supply (V)	Operating Status	Indoor unit					Unit Capacity					Total				Outdoor noise (dB)	
		A	B	C	D	E	A	B	C	D	E	Cooling capacity (kW)	Power consumption (W)	Operating current (A)	Sound Pressure	Sound Power	
220	1 unit	07	—	—	—	—	2.7	—	—	—	—	2.7 (0.8– 4.8)	900 (300–1980)	4.70 (1.87– 9.18)	54	69	
		10	—	—	—	—	4.0	—	—	—	—	4.0 (0.8– 5.2)	1450 (300–1980)	6.94 (1.87– 9.18)	54	69	
		13	—	—	—	—	5.0	—	—	—	—	5.0 (0.8– 6.5)	2050 (310–2750)	9.81 (1.93–12.76)	54	69	
		16	—	—	—	—	5.5	—	—	—	—	5.5 (0.8– 6.9)	2400 (310–3000)	11.48 (1.93–13.91)	54	69	
		18	—	—	—	—	6.0	—	—	—	—	6.0 (0.8– 7.1)	2630 (310–3200)	12.58 (1.93–14.84)	54	69	
		22	—	—	—	—	7.0	—	—	—	—	7.0 (1.8– 8.2)	2700 (330–3600)	12.78 (2.05–16.70)	54	69	
		24	—	—	—	—	8.1	—	—	—	—	8.1 (1.8– 8.6)	3300 (330–3700)	15.63 (2.05–17.16)	54	69	
		07	07	—	—	—	2.70	2.70	—	—	—	5.4 (1.5– 7.4)	2050 (320–3200)	9.81 (1.94–14.84)	54	69	
		10	07	—	—	—	4.00	2.70	—	—	—	6.7 (1.5– 8.9)	2080 (320–3200)	9.95 (1.94–14.84)	54	69	
		13	07	—	—	—	4.81	2.59	—	—	—	7.4 (1.5–10.1)	2320 (320–3210)	11.10 (1.94–14.89)	54	69	
	2 units	16	07	—	—	—	5.10	2.50	—	—	—	7.6 (1.5–10.1)	2480 (320–3230)	11.87 (1.94–14.98)	54	69	
		18	07	—	—	—	5.45	2.45	—	—	—	7.9 (1.5–10.1)	2480 (320–3230)	11.87 (1.94–14.98)	54	69	
		22	07	—	—	—	5.70	2.20	—	—	—	7.9 (1.5–10.1)	2480 (320–3230)	11.87 (1.94–14.98)	54	69	
		24	07	—	—	—	6.23	2.08	—	—	—	8.3 (1.5–10.2)	2700 (320–3240)	12.92 (1.94–15.03)	54	69	
		10	10	—	—	—	3.60	3.60	—	—	—	7.2 (1.5–10.0)	2100 (320–3200)	10.05 (1.94–14.84)	54	69	
		13	10	—	—	—	4.22	3.38	—	—	—	7.6 (1.5–10.1)	2320 (320–3210)	11.10 (1.94–14.89)	54	69	
		16	10	—	—	—	4.57	3.33	—	—	—	7.9 (1.5–10.1)	2480 (320–3230)	11.87 (1.94–14.98)	54	69	
		18	10	—	—	—	4.74	3.16	—	—	—	7.9 (1.5–10.1)	2480 (320–3230)	11.87 (1.94–14.98)	54	69	
		22	10	—	—	—	5.28	3.02	—	—	—	8.3 (1.5–10.2)	2700 (320–3240)	12.92 (1.94–15.03)	54	69	
		24	10	—	—	—	5.76	2.84	—	—	—	8.6 (1.5–10.2)	2860 (320–3250)	13.68 (1.94–15.07)	54	69	
		13	13	—	—	—	3.95	3.95	—	—	—	7.9 (1.5–10.1)	2480 (320–3230)	11.87 (1.94–14.98)	54	69	
		16	13	—	—	—	4.35	3.95	—	—	—	8.3 (1.5–10.2)	2700 (320–3240)	12.92 (1.94–15.03)	54	69	
		18	13	—	—	—	4.53	3.77	—	—	—	8.3 (1.5–10.2)	2700 (320–3240)	12.92 (1.94–15.03)	54	69	
		22	13	—	—	—	5.02	3.58	—	—	—	8.6 (1.5–10.2)	2860 (320–3250)	13.68 (1.94–15.07)	54	69	
		24	13	—	—	—	5.32	3.28	—	—	—	8.6 (1.5–10.2)	2860 (320–3250)	13.68 (1.94–15.07)	54	69	
		16	16	—	—	—	4.30	4.30	—	—	—	8.6 (1.5–10.2)	2860 (320–3250)	13.68 (1.94–15.07)	54	69	
		18	16	—	—	—	4.49	4.11	—	—	—	8.6 (1.5–10.2)	2860 (320–3250)	13.68 (1.94–15.07)	54	69	
		22	16	—	—	—	4.82	3.78	—	—	—	8.6 (1.5–10.2)	2860 (320–3250)	13.68 (1.94–15.07)	54	69	
		24	16	—	—	—	5.12	3.48	—	—	—	8.6 (1.5–10.2)	2860 (320–3250)	13.68 (1.94–15.07)	54	69	
		18	18	—	—	—	4.30	4.30	—	—	—	8.6 (1.5–10.2)	2860 (320–3250)	13.68 (1.94–15.07)	54	69	
		22	18	—	—	—	4.63	3.97	—	—	—	8.6 (1.5–10.2)	2860 (320–3250)	13.68 (1.94–15.07)	54	69	
		24	18	—	—	—	4.94	3.66	—	—	—	8.6 (1.5–10.2)	2860 (320–3250)	13.68 (1.94–15.07)	54	69	
		22	22	—	—	—	4.50	4.50	—	—	—	9.0 (1.5–10.6)	2200 (320–2590)	10.42 (1.94–12.01)	54	69	
		24	24	—	—	—	4.17	4.83	—	—	—	9.0 (1.5–10.6)	2200 (320–2590)	10.42 (1.94–12.01)	54	69	
		24	24	—	—	—	4.55	4.55	—	—	—	9.1 (1.5–10.7)	2220 (320–2610)	10.51 (1.94–12.11)	54	69	
	3 units	07	07	07	—	—	2.70	2.70	2.70	—	—	8.1 (2.0–10.4)	2290 (380–2750)	10.96 (2.16–12.76)	54	69	
		10	07	07	—	—	3.53	2.38	2.38	—	—	8.3 (2.0–10.4)	2300 (380–2750)	11.00 (2.16–12.76)	54	69	
		13	07	07	—	—	4.13	2.23	2.23	—	—	8.6 (2.0–10.4)	2300 (380–2750)	11.00 (2.16–12.76)	54	69	
		16	07	07	—	—	4.39	2.16	2.16	—	—	8.7 (2.0–10.5)	2350 (380–2760)	11.24 (2.16–12.80)	54	69	
		18	07	07	—	—	4.58	2.06	2.06	—	—	8.7 (2.0–10.5)	2350 (380–2760)	11.24 (2.16–12.80)	54	69	
		22	07	07	—	—	4.91	1.89	1.89	—	—	8.7 (2.0–10.5)	2350 (380–2760)	11.24 (2.16–12.80)	54	69	
		24	07	07	—	—	5.22	1.74	1.74	—	—	8.7 (2.0–10.5)	2350 (380–2760)	11.24 (2.16–12.80)	54	69	
		10	10	07	—	—	3.18	3.18	2.14	—	—	8.5 (2.0–10.4)	2300 (380–2750)	11.00 (2.16–12.76)	54	69	
		13	10	07	—	—	3.72	2.97	2.01	—	—	8.7 (2.0–10.5)	2350 (380–2760)	11.24 (2.16–12.80)	54	69	
		16	10	07	—	—	3.92	2.85	1.93	—	—	8.7 (2.0–10.5)	2350 (380–2760)	11.24 (2.16–12.80)	54	69	
		18	10	07	—	—	4.11	2.74	1.85	—	—	8.7 (2.0–10.5)	2350 (380–2760)	11.24 (2.16–12.80)	54	69	
		22	10	07	—	—	4.50	2.57	1.73	—	—	8.8 (2.0–10.6)	2400 (380–2780)	11.48 (2.16–12.89)	54	69	
		24	10	07	—	—	4.82	2.38	1.61	—	—	8.8 (2.0–10.6)	2400 (380–2780)	11.48 (2.16–12.89)	54	69	
		13	13	07	—	—	3.43	3.43	1.85	—	—	8.7 (2.0–10.5)	2350 (380–2760)	11.24 (2.16–12.80)	54	69	
		16	13	07	—	—	3.67	3.33	1.80	—	—	8.8 (2.0–10.6)	2400 (380–2780)	11.48 (2.16–12.89)	54	69	
		18	13	07	—	—	3.85	3.21	1.73	—	—	8.8 (2.0–10.6)	2400 (380–2780)	11.48 (2.16–12.89)	54	69	
		22	13	07	—	—	4.24	3.03	1.63	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.72 (2.16–12.94)	54	69	
		24	13	07	—	—	4.56	2.82	1.52	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.72 (2.16–12.94)	54	69	
		16	16	07	—	—	3.57	3.57	1.75	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.72 (2.16–12.94)	54	69	
		18	16	07	—	—	3.76	3.45	1.69	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.72 (2.16–12.94)	54	69	
		22	16	07	—	—	4.10	3.22	1.58	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.72 (2.16–12.94)	54	69	
		24	16	07	—	—	4.42	3.00	1.47	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.72 (2.16–12.94)	54	69	
		18	18	07	—	—	3.63	3.63	1.63	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.72 (2.16–12.94)	54	69	
		22	18	07	—	—	3.97	3.40	1.53	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.72 (2.16–12.94)	54	69	
		24	18	07	—	—	4.29	3.18	1.43	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.72 (2.16–12.94)	54	69	
		10	10	10	—	—	2.87	2.87	2.87	—	—	8.6 (2.0–10.4)	2300 (380–2750)	11.00 (2.16–12.76)	54	69	
		13	10	10	—	—	3.35	2.68	2.68	—	—	8.7 (2.0–10.5)	2350 (380–2760)	11.24 (2.16–12.80)	54	69	
		16	10	10	—	—	3.54	2.58	2.58	—	—	8.7 (2.0–10.5)	2350 (380–2760)	11.24 (2.16–12.80)	54	69	
		18	10	10	—	—	3.73	2.49	2.49	—	—	8.7 (2.0–10.5)	2350 (380–2760)	11.24 (2.16–12.80)	54	69	
		22	10	10	—	—	4.15	2.37	2.37	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.72 (2.16–12.94)	54	69	
		24	10	10	—	—	4.48	2.21	2.21	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.72 (2.16–12.94)	54	69	
		13	13	10	—	—	3.11	3.11	2.49	—	—	8.7 (2.0–10.5)	2350 (380–2760)	11.24 (2.16–12.80)	54	69	
		16	13	10	—	—	3.34	3.03	2.43	—	—	8.8 (2.0–10.6)	2400 (380–2780)	11.48 (2.16–12.89)	54	69	
		18	13	10	—	—	3.56	2.97	2.37	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.72 (2.16–12.94)	54	69	
		22	13	10	—	—	3.89	2.78	2.23	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.72 (2.16–12.94)	54	69	
		24	13	10	—	—	4.22	2.60	2.08	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.72 (2.16–12.94)	54	69	
		16	16	10	—	—	3.26	3.26	2.37	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.72 (2.16–12.94)	54	69	
		18	16	10	—	—	3.45	3.16	2.30	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.72 (2.16–12.94)	54	69	
		22	16	10	—	—	3.78	2.97	2.16	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.72 (2.16–12.94)	54	69	
24		16	10	—	—	4.10	2.78	2.02	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.72 (2.16–12.94)	54	69		
18	18	10	—	—	3.34	3.34	2.23	—	—	8.9 (							

<Heating / 220V> (Continued)

Power supply (V)	Operating Status	Indoor unit					Unit Capacity					Total			Outdoor noise (dB)	
		A	B	C	D	E	A	B	C	D	E	Cooling capacity (kW)	Power consumption (W)	Operating current (A)	Sound Pressure	Sound Power
220	4 units	07 07 07 07 —	2.33	2.33	2.33	2.33	—	9.3 (2.2-11.5)	2330 (450-2850)	11.15 (2.56-13.22)	54	69				
		10 07 07 07 —	3.11	2.10	2.10	2.10	—	9.4 (2.2-11.5)	2340 (460-2850)	11.20 (2.61-13.22)	54	69				
		13 07 07 07 —	3.66	1.98	1.98	1.98	—	9.6 (2.2-11.6)	2360 (470-2860)	11.29 (2.67-13.27)	54	69				
		16 07 07 07 —	3.92	1.93	1.93	1.93	—	9.7 (2.2-11.6)	2370 (470-2880)	11.34 (2.67-13.36)	54	69				
		18 07 07 07 —	4.17	1.88	1.88	1.88	—	9.8 (2.2-11.6)	2380 (480-2880)	11.39 (2.73-13.36)	54	69				
		22 07 07 07 —	4.64	1.79	1.79	1.79	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		24 07 07 07 —	5.00	1.67	1.67	1.67	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		10 10 07 07 —	2.84	2.84	1.91	1.91	—	9.5 (2.2-11.5)	2350 (460-2850)	11.24 (2.61-13.22)	54	69				
		13 10 07 07 —	3.37	2.69	1.82	1.82	—	9.7 (2.2-11.6)	2370 (470-2880)	11.34 (2.67-13.36)	54	69				
		16 10 07 07 —	3.62	2.63	1.78	1.78	—	9.8 (2.2-11.6)	2380 (480-2880)	11.39 (2.73-13.36)	54	69				
		18 10 07 07 —	3.86	2.57	1.74	1.74	—	9.9 (2.2-11.7)	2390 (480-2900)	11.44 (2.73-13.45)	54	69				
		22 10 07 07 —	4.27	2.44	1.65	1.65	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		24 10 07 07 —	4.63	2.29	1.54	1.54	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		13 13 07 07 —	3.21	3.21	1.74	1.74	—	9.9 (2.2-11.7)	2390 (480-2900)	11.44 (2.73-13.45)	54	69				
		16 13 07 07 —	3.46	3.14	1.70	1.70	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		18 13 07 07 —	3.66	3.05	1.65	1.65	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		22 13 07 07 —	4.02	2.87	1.55	1.55	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		24 13 07 07 —	4.38	2.70	1.46	1.46	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		16 16 07 07 —	3.35	3.35	1.65	1.65	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		18 16 07 07 —	3.55	3.25	1.60	1.60	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		22 16 07 07 —	3.91	3.07	1.51	1.51	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		24 16 07 07 —	4.26	2.89	1.42	1.42	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		18 18 07 07 —	3.45	3.45	1.55	1.55	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		22 18 07 07 —	3.80	3.26	1.47	1.47	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		24 18 07 07 —	4.15	3.08	1.38	1.38	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		10 10 10 07 —	2.61	2.61	2.61	1.76	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		13 10 10 07 —	3.12	2.50	2.50	1.69	—	9.6 (2.2-11.6)	2360 (470-2880)	11.29 (2.67-13.36)	54	69				
		16 10 10 07 —	3.36	2.44	2.44	1.65	—	9.8 (2.2-11.6)	2380 (480-2880)	11.39 (2.73-13.36)	54	69				
		18 10 10 07 —	3.59	2.40	2.40	1.62	—	9.9 (2.2-11.7)	2390 (480-2900)	11.44 (2.73-13.45)	54	69				
		22 10 10 07 —	3.95	2.26	2.26	1.53	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		24 10 10 07 —	4.31	2.13	2.13	1.44	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		13 13 10 07 —	2.99	2.99	2.40	1.62	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		16 13 10 07 —	3.20	2.91	2.33	1.57	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		18 13 10 07 —	3.39	2.82	2.26	1.53	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		22 13 10 07 —	3.74	2.67	2.14	1.44	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		24 13 10 07 —	4.09	2.53	2.02	1.36	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		16 16 10 07 —	3.11	3.11	2.26	1.53	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		18 16 10 07 —	3.30	3.02	2.20	1.48	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		22 16 10 07 —	3.65	2.86	2.08	1.41	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		24 16 10 07 —	3.99	2.71	1.97	1.33	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		18 18 10 07 —	3.21	3.21	2.14	1.44	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		22 18 10 07 —	3.55	3.05	2.03	1.37	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		24 18 10 07 —	3.89	2.88	1.92	1.30	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		13 13 13 07 —	2.82	2.82	2.82	1.53	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		16 13 13 07 —	3.02	2.75	2.75	1.48	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		18 13 13 07 —	3.21	2.67	2.67	1.44	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		22 13 13 07 —	3.55	2.54	2.54	1.37	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		24 13 13 07 —	3.89	2.40	2.40	1.30	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		16 16 13 07 —	2.94	2.94	2.67	1.44	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		18 16 13 07 —	3.13	2.86	2.60	1.41	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		22 16 13 07 —	3.47	2.72	2.48	1.34	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		24 16 13 07 —	3.80	2.58	2.35	1.27	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		18 18 13 07 —	3.05	3.05	2.54	1.37	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		22 18 13 07 —	3.38	2.90	2.42	1.30	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		24 18 13 07 —	3.72	2.75	2.29	1.24	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		10 10 10 10 —	2.43	2.43	2.43	2.43	—	9.7 (2.2-11.6)	2370 (470-2780)	11.34 (2.67-12.89)	54	69				
		13 10 10 10 —	2.91	2.33	2.33	2.33	—	9.9 (2.2-11.7)	2390 (480-2900)	11.44 (2.73-13.45)	54	69				
		16 10 10 10 —	3.14	2.29	2.29	2.29	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		18 10 10 10 —	3.33	2.22	2.22	2.22	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		22 10 10 10 —	3.68	2.11	2.11	2.11	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		24 10 10 10 —	4.03	1.99	1.99	1.99	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		13 13 10 10 —	2.78	2.78	2.22	2.22	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		16 13 10 10 —	2.97	2.70	2.16	2.16	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		22 13 10 10 —	3.50	2.50	2.00	2.00	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		24 13 10 10 —	3.84	2.37	1.90	1.90	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		16 16 10 10 —	2.89	2.89	2.11	2.11	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
		18 13 10 10 —	3.16	2.63	2.11	2.11	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69				
22 16 10 10 —	3.41	2.68	1.95	1.95	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69						
24 16 10 10 —	3.75	2.55	1.85	1.85	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69						
18 16 10 10 —	3.08	2.82	2.05	2.05	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69						
18 18 10 10 —	3.00	3.00	2.00	2.00	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69						
22 18 10 10 —	3.33	2.86	1.90	1.90	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69						
24 18 10 10 —	3.67	2.71	1.81	1.81	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69						
13 13 13 10 —	2.63	2.63	2.63	2.11	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69						
16 13 13 10 —	2.82	2.56	2.56	2.05	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69						
22 13 13 10 —	3.33	2.38	2.38	1.90	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69						
24 13 13 10 —	3.67	2.26	2.26	1.81	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69						
16 16 13 10 —	2.75	2.75	2.50	2.00	—	10.0 (2.2-11.7)	2400 (490-2900)	11.48 (2.78-13.45)	54	69						
22 16																

<Heating / 220V> (Continued)

Power supply (V)	Operating Status	Indoor unit					Unit Capacity					Total			Outdoor noise (dB)	
		A	B	C	D	E	A	B	C	D	E	Cooling capacity (kW)	Power consumption (W)	Operating current (A)	Sound Pressure	Sound Power
220	5 units	07	07	07	07	07	2.28	2.28	2.28	2.28	2.28	11.4 (3.4-13.4)	2690 (775-4020)	12.87 (4.40-18.65)	54	69
		10	07	07	07	07	3.16	2.13	2.13	2.13	2.13	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		13	07	07	07	07	3.70	2.00	2.00	2.00	2.00	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		16	07	07	07	07	3.95	1.94	1.94	1.94	1.94	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		18	07	07	07	07	4.18	1.88	1.88	1.88	1.88	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		10	10	07	07	07	2.91	2.91	1.96	1.96	1.96	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		13	10	07	07	07	3.42	2.74	1.85	1.85	1.85	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		16	10	07	07	07	3.66	2.66	1.79	1.79	1.79	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		18	10	07	07	07	3.88	2.59	1.75	1.75	1.75	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		13	13	07	07	07	3.23	3.23	1.75	1.75	1.75	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		16	13	07	07	07	3.46	3.15	1.70	1.70	1.70	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		18	13	07	07	07	3.68	3.06	1.65	1.65	1.65	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		16	16	07	07	07	3.37	3.37	1.65	1.65	1.65	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		18	16	07	07	07	3.58	3.28	1.61	1.61	1.61	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		10	10	10	07	07	2.69	2.69	2.69	1.82	1.82	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		13	10	10	07	07	3.18	2.54	2.54	1.72	1.72	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		13	13	10	07	07	3.02	3.02	2.41	1.63	1.63	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		16	10	10	07	07	3.40	2.48	2.48	1.67	1.67	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		18	10	10	07	07	3.62	2.41	2.41	1.63	1.63	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		13	13	13	07	07	2.87	2.87	2.87	1.55	1.55	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		16	13	13	07	07	3.08	2.80	2.80	1.51	1.51	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		18	13	13	07	07	3.28	2.73	2.73	1.48	1.48	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		16	16	10	07	07	3.15	3.15	2.29	1.55	1.55	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		18	16	10	07	07	3.36	3.08	2.24	1.51	1.51	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		16	16	13	07	07	3.01	3.01	2.73	1.48	1.48	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		18	16	13	07	07	3.21	2.94	2.67	1.44	1.44	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		10	10	10	10	10	2.50	2.50	2.50	2.50	1.69	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		13	10	10	10	10	2.97	2.38	2.38	2.38	1.60	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		16	10	10	10	10	3.19	2.32	2.32	2.32	1.56	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		18	10	10	10	10	3.39	2.26	2.26	2.26	1.53	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		13	13	10	10	10	2.83	2.83	2.26	2.26	1.53	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		16	13	10	10	10	3.04	2.76	2.21	2.21	1.49	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		18	13	10	10	10	3.24	2.70	2.16	2.16	1.46	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		16	16	10	10	10	2.97	2.97	2.16	2.16	1.46	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		13	13	13	10	10	2.70	2.70	2.70	2.16	1.46	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		16	13	13	10	10	2.90	2.64	2.64	2.11	1.42	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		16	16	13	10	10	2.83	2.83	2.58	2.06	1.39	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		13	13	13	13	10	2.58	2.58	2.58	2.58	1.39	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		16	13	13	13	10	2.77	2.52	2.52	2.52	1.36	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		16	16	13	13	10	2.72	2.72	2.47	2.47	1.33	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		10	10	10	10	10	2.34	2.34	2.34	2.34	2.34	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		13	10	10	10	10	2.79	2.23	2.23	2.23	2.23	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		16	10	10	10	10	2.99	2.18	2.18	2.18	2.18	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		18	10	10	10	10	3.19	2.13	2.13	2.13	2.13	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		13	13	10	10	10	2.66	2.66	2.13	2.13	2.13	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		16	13	10	10	10	2.86	2.60	2.08	2.08	2.08	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		18	13	10	10	10	3.05	2.54	2.03	2.03	2.03	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		16	16	10	10	10	2.80	2.80	2.03	2.03	2.03	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		13	13	13	10	10	2.54	2.54	2.54	2.03	2.03	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		16	13	13	10	10	2.74	2.49	2.49	1.99	1.99	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		18	13	13	10	10	2.93	2.44	2.44	1.95	1.95	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		16	16	13	10	10	2.75	2.75	2.50	2.00	2.00	12.0 (3.4-14.0)	2833 (775-4200)	13.56 (4.40-19.48)	54	69
		13	13	13	13	10	2.44	2.44	2.44	2.44	1.95	11.7 (3.4-13.7)	2762 (775-4120)	13.22 (4.40-19.11)	54	69
		16	13	13	13	10	2.69	2.45	2.45	2.45	1.96	12.0 (3.4-14.0)	2833 (775-4200)	13.56 (4.40-19.48)	54	69
		18	13	13	13	10	2.88	2.40	2.40	2.40	1.92	12.0 (3.4-14.0)	2833 (775-4200)	13.56 (4.40-19.48)	54	69
		16	16	13	13	10	2.64	2.64	2.40	2.40	1.92	12.0 (3.4-14.0)	2833 (775-4200)	13.56 (4.40-19.48)	54	69
		13	13	13	13	13	2.40	2.40	2.40	2.40	2.40	12.0 (3.4-14.0)	2833 (775-4200)	13.56 (4.40-19.48)	54	69
		16	13	13	13	13	2.59	2.35	2.35	2.35	2.35	12.0 (3.4-14.0)	2833 (775-4200)	13.56 (4.40-19.48)	54	69
		22	07*	07*	07*	07*	4.72	1.82	1.82	1.82	1.82	12.0 (3.4-14.0)	2833 (775-4200)	13.56 (4.40-19.48)	54	69
		22	10*	07*	07*	07*	4.40	2.51	1.70	1.70	1.70	12.0 (3.4-14.0)	2833 (775-4200)	13.56 (4.40-19.48)	54	69
		22	10*	10*	07*	07*	4.12	2.35	2.35	1.59	1.59	12.0 (3.4-14.0)	2833 (775-4200)	13.56 (4.40-19.48)	54	69
		22	10*	10*	10*	07*	3.87	2.21	2.21	2.21	1.49	12.0 (3.4-14.0)	2833 (775-4200)	13.56 (4.40-19.48)	54	69
		22	10*	10*	10*	10*	3.65	2.09	2.09	2.09	2.09	12.0 (3.4-14.0)	2833 (775-4200)	13.56 (4.40-19.48)	54	69
		22	13*	07*	07*	07*	4.18	2.99	1.61	1.61	1.61	12.0 (3.4-14.0)	2833 (775-4200)	13.56 (4.40-19.48)	54	69
		22	13*	10*	07*	07*	3.93	2.80	2.24	1.51	1.51	12.0 (3.4-14.0)	2833 (775-4200)	13.56 (4.40-19.48)	54	69
		22	13*	10*	10*	07*	3.70	2.64	2.11	2.11	1.43	12.0 (3.4-14.0)	2833 (775-4200)	13.56 (4.40-19.48)	54	69
		22	13*	10*	10*	10*	3.50	2.50	2.00	2.00	2.00	12.0 (3.4-14.0)	2833 (775-4200)	13.56 (4.40-19.48)	54	69
		22	13*	13*	07*	07*	3.75	2.68	2.68	1.45	1.45	12.0 (3.4-14.0)	2833 (775-4200)	13.56 (4.40-19.48)	54	69
		22	13*	13*	10*	07*	3.54	2.53	2.53	2.03	1.37	12.0 (3.4-14.0)	2833 (775-4200)	13.56 (4.40-19.48)	54	69
		22	13*	13*	10*	10*	3.36	2.40	2.40	1.92	1.92	12.0 (3.4-14.0)	2833 (775-4200)	13.56 (4.40-19.48)	54	69</

<Heating / 230V>

Power supply (V)	Operating Status	Indoor unit					Unit Capacity					Total			Outdoor noise (dB)	
		A	B	C	D	E	A	B	C	D	E	Cooling capacity (kW)	Power consumption (W)	Operating current (A)	Sound Pressure	Sound Power
230	1 unit	07	—	—	—	—	2.7	—	—	—	—	2.7 (0.8– 4.8)	900 (300–1980)	4.50 (1.79– 8.78)	54	69
		10	—	—	—	—	4.0	—	—	—	—	4.0 (0.8– 5.2)	1450 (300–1980)	6.64 (1.79– 8.78)	54	69
		13	—	—	—	—	5.0	—	—	—	—	5.0 (0.8– 6.5)	2050 (310–2750)	9.38 (1.85–12.20)	54	69
		16	—	—	—	—	5.5	—	—	—	—	5.5 (0.8– 6.9)	2400 (310–3000)	10.98 (1.85–13.31)	54	69
		18	—	—	—	—	6.0	—	—	—	—	6.0 (0.8– 7.1)	2630 (310–3200)	12.04 (1.85–14.20)	54	69
		22	—	—	—	—	7.0	—	—	—	—	7.0 (1.8– 8.2)	2700 (330–3600)	12.23 (1.97–15.97)	54	69
		24	—	—	—	—	8.1	—	—	—	—	8.1 (1.8– 8.6)	3300 (330–3700)	14.95 (1.97–16.42)	54	69
		07	07	—	—	—	2.70	2.70	—	—	—	5.4 (1.5– 7.4)	2050 (320–3200)	9.38 (1.86–14.20)	54	69
		10	07	—	—	—	4.00	2.70	—	—	—	6.7 (1.5– 8.9)	2080 (320–3200)	9.52 (1.86–14.20)	54	69
		13	07	—	—	—	4.81	2.59	—	—	—	7.4 (1.5–10.1)	2320 (320–3210)	10.62 (1.86–14.24)	54	69
	2 units	16	07	—	—	—	5.10	2.50	—	—	—	7.6 (1.5–10.1)	2480 (320–3230)	11.35 (1.86–14.33)	54	69
		18	07	—	—	—	5.45	2.45	—	—	—	7.9 (1.5–10.1)	2480 (320–3230)	11.35 (1.86–14.33)	54	69
		22	07	—	—	—	5.70	2.20	—	—	—	7.9 (1.5–10.1)	2480 (320–3230)	11.35 (1.86–14.33)	54	69
		24	07	—	—	—	6.23	2.08	—	—	—	8.3 (1.5–10.2)	2700 (320–3240)	12.36 (1.86–14.37)	54	69
		10	10	—	—	—	3.60	3.60	—	—	—	7.2 (1.5–10.0)	2100 (320–3200)	9.61 (1.86–14.20)	54	69
		13	10	—	—	—	4.22	3.38	—	—	—	7.6 (1.5–10.1)	2320 (320–3210)	10.62 (1.86–14.24)	54	69
		16	10	—	—	—	4.57	3.33	—	—	—	7.9 (1.5–10.1)	2480 (320–3230)	11.35 (1.86–14.33)	54	69
		18	10	—	—	—	4.74	3.16	—	—	—	7.9 (1.5–10.1)	2480 (320–3230)	11.35 (1.86–14.33)	54	69
		22	10	—	—	—	5.28	3.02	—	—	—	8.3 (1.5–10.2)	2700 (320–3240)	12.36 (1.86–14.37)	54	69
		24	10	—	—	—	5.76	2.84	—	—	—	8.6 (1.5–10.2)	2860 (320–3250)	13.09 (1.86–14.42)	54	69
		13	13	—	—	—	3.95	3.95	—	—	—	7.9 (1.5–10.1)	2480 (320–3230)	11.35 (1.86–14.33)	54	69
		16	13	—	—	—	4.35	3.95	—	—	—	8.3 (1.5–10.2)	2700 (320–3240)	12.36 (1.86–14.37)	54	69
		18	13	—	—	—	4.53	3.77	—	—	—	8.3 (1.5–10.2)	2700 (320–3240)	12.36 (1.86–14.37)	54	69
		22	13	—	—	—	5.02	3.58	—	—	—	8.6 (1.5–10.2)	2860 (320–3250)	13.09 (1.86–14.42)	54	69
		24	13	—	—	—	5.32	3.28	—	—	—	8.6 (1.5–10.2)	2860 (320–3250)	13.09 (1.86–14.42)	54	69
		16	16	—	—	—	4.30	4.30	—	—	—	8.6 (1.5–10.2)	2860 (320–3250)	13.09 (1.86–14.42)	54	69
		18	16	—	—	—	4.49	4.11	—	—	—	8.6 (1.5–10.2)	2860 (320–3250)	13.09 (1.86–14.42)	54	69
		22	16	—	—	—	4.82	3.78	—	—	—	8.6 (1.5–10.2)	2860 (320–3250)	13.09 (1.86–14.42)	54	69
		24	16	—	—	—	5.12	3.48	—	—	—	8.6 (1.5–10.2)	2860 (320–3250)	13.09 (1.86–14.42)	54	69
		18	18	—	—	—	4.30	4.30	—	—	—	8.6 (1.5–10.2)	2860 (320–3250)	13.09 (1.86–14.42)	54	69
		22	18	—	—	—	4.63	3.97	—	—	—	8.6 (1.5–10.2)	2860 (320–3250)	13.09 (1.86–14.42)	54	69
		24	18	—	—	—	4.94	3.66	—	—	—	8.6 (1.5–10.2)	2860 (320–3250)	13.09 (1.86–14.42)	54	69
		22	22	—	—	—	4.50	4.50	—	—	—	9.0 (1.5–10.6)	2200 (320–2590)	9.96 (1.86–11.49)	54	69
		22	24	—	—	—	4.17	4.83	—	—	—	9.0 (1.5–10.6)	2200 (320–2590)	9.96 (1.86–11.49)	54	69
		24	24	—	—	—	4.55	4.55	—	—	—	9.1 (1.5–10.7)	2220 (320–2610)	10.05 (1.86–11.58)	54	69
	3 units	07	07	07	—	—	2.70	2.70	2.70	—	—	8.1 (2.0–10.4)	2290 (380–2750)	10.48 (2.07–12.20)	54	69
		10	07	07	—	—	3.53	2.38	2.38	—	—	8.3 (2.0–10.4)	2300 (380–2750)	10.53 (2.07–12.20)	54	69
		13	07	07	—	—	4.13	2.23	2.23	—	—	8.6 (2.0–10.4)	2300 (380–2750)	10.53 (2.07–12.20)	54	69
		16	07	07	—	—	4.39	2.16	2.16	—	—	8.7 (2.0–10.5)	2350 (380–2760)	10.76 (2.07–12.24)	54	69
		18	07	07	—	—	4.58	2.06	2.06	—	—	8.7 (2.0–10.5)	2350 (380–2760)	10.76 (2.07–12.24)	54	69
		22	07	07	—	—	4.91	1.89	1.89	—	—	8.7 (2.0–10.5)	2350 (380–2760)	10.76 (2.07–12.24)	54	69
		24	07	07	—	—	5.22	1.74	1.74	—	—	8.7 (2.0–10.5)	2350 (380–2760)	10.76 (2.07–12.24)	54	69
		10	10	07	—	—	3.18	3.18	2.14	—	—	8.5 (2.0–10.4)	2300 (380–2750)	10.53 (2.07–12.20)	54	69
		13	10	07	—	—	3.72	2.97	2.01	—	—	8.7 (2.0–10.5)	2350 (380–2760)	10.76 (2.07–12.24)	54	69
		16	10	07	—	—	3.92	2.85	1.93	—	—	8.7 (2.0–10.5)	2350 (380–2760)	10.76 (2.07–12.24)	54	69
		18	10	07	—	—	4.11	2.74	1.85	—	—	8.7 (2.0–10.5)	2350 (380–2760)	10.76 (2.07–12.24)	54	69
		22	10	07	—	—	4.50	2.57	1.73	—	—	8.8 (2.0–10.6)	2400 (380–2780)	10.98 (2.07–12.33)	54	69
		24	10	07	—	—	4.82	2.38	1.61	—	—	8.8 (2.0–10.6)	2400 (380–2780)	10.98 (2.07–12.33)	54	69
		13	13	07	—	—	3.43	3.43	1.85	—	—	8.7 (2.0–10.5)	2350 (380–2760)	10.76 (2.07–12.24)	54	69
		16	13	07	—	—	3.67	3.33	1.80	—	—	8.8 (2.0–10.6)	2400 (380–2780)	10.98 (2.07–12.33)	54	69
		18	13	07	—	—	3.85	3.21	1.73	—	—	8.8 (2.0–10.6)	2400 (380–2780)	10.98 (2.07–12.33)	54	69
		22	13	07	—	—	4.24	3.03	1.63	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.21 (2.07–12.38)	54	69
		24	13	07	—	—	4.56	2.82	1.52	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.21 (2.07–12.38)	54	69
		16	16	07	—	—	3.57	3.57	1.75	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.21 (2.07–12.38)	54	69
		18	16	07	—	—	3.76	3.45	1.69	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.21 (2.07–12.38)	54	69
		22	16	07	—	—	4.10	3.22	1.58	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.21 (2.07–12.38)	54	69
		24	16	07	—	—	4.42	3.00	1.47	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.21 (2.07–12.38)	54	69
		18	18	07	—	—	3.63	3.63	1.63	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.21 (2.07–12.38)	54	69
		22	18	07	—	—	3.97	3.40	1.53	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.21 (2.07–12.38)	54	69
		24	18	07	—	—	4.29	3.18	1.43	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.21 (2.07–12.38)	54	69
		10	10	10	—	—	2.87	2.87	2.87	—	—	8.6 (2.0–10.4)	2300 (380–2750)	10.53 (2.07–12.20)	54	69
		13	10	10	—	—	3.35	2.68	2.68	—	—	8.7 (2.0–10.5)	2350 (380–2760)	10.76 (2.07–12.24)	54	69
		16	10	10	—	—	3.54	2.58	2.58	—	—	8.7 (2.0–10.5)	2350 (380–2760)	10.76 (2.07–12.24)	54	69
		18	10	10	—	—	3.73	2.49	2.49	—	—	8.7 (2.0–10.5)	2350 (380–2760)	10.76 (2.07–12.24)	54	69
		22	10	10	—	—	4.15	2.37	2.37	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.21 (2.07–12.38)	54	69
		24	10	10	—	—	4.48	2.21	2.21	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.21 (2.07–12.38)	54	69
		13	13	10	—	—	3.11	3.11	2.49	—	—	8.7 (2.0–10.5)	2350 (380–2760)	10.76 (2.07–12.24)	54	69
		16	13	10	—	—	3.34	3.03	2.43	—	—	8.8 (2.0–10.6)	2400 (380–2780)	10.98 (2.07–12.33)	54	69
		18	13	10	—	—	3.56	2.97	2.37	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.21 (2.07–12.38)	54	69
		22	13	10	—	—	3.89	2.78	2.23	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.21 (2.07–12.38)	54	69
		24	13	10	—	—	4.22	2.60	2.08	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.21 (2.07–12.38)	54	69
		16	16	10	—	—	3.26	3.26	2.37	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.21 (2.07–12.38)	54	69
		18	16	10	—	—	3.45	3.16	2.30	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.21 (2.07–12.38)	54	69
		22	16	10	—	—	3.78	2.97	2.16	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.21 (2.07–12.38)	54	69
		24	16	10	—	—	4.10	2.78	2.02	—	—	8.9 (2.0–10.7)	2450 (380–2790)	11.21 (2.07–12.38)	54	69
	18	18	10	—	—	3.34	3.34	2.23	—	—	8.9 (2.0–10.7)	2450 (				

<Heating / 230V> (Continued)

Power supply (V)	Operating Status	Indoor unit					Unit Capacity					Total			Outdoor noise (dB)	
		A	B	C	D	E	A	B	C	D	E	Cooling capacity (kW)	Power consumption (W)	Operating current (A)	Sound Pressure	Sound Power
230	4 units	07 07 07 07 —	2.33	2.33	2.33	2.33	—	9.3 (2.2–11.5)	2330 (450–2850)	10.66 (2.45–12.64)	54	69				
		10 07 07 07 —	3.11	2.10	2.10	2.10	—	9.4 (2.2–11.5)	2340 (450–2850)	10.71 (2.50–12.64)	54	69				
		13 07 07 07 —	3.66	1.98	1.98	1.98	—	9.6 (2.2–11.6)	2360 (470–2860)	10.80 (2.55–12.69)	54	69				
		16 07 07 07 —	3.92	1.93	1.93	1.93	—	9.7 (2.2–11.6)	2370 (470–2880)	10.85 (2.55–12.78)	54	69				
		18 07 07 07 —	4.17	1.88	1.88	1.88	—	9.8 (2.2–11.6)	2380 (480–2880)	10.89 (2.61–12.78)	54	69				
		22 07 07 07 —	4.64	1.79	1.79	1.79	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		24 07 07 07 —	5.00	1.67	1.67	1.67	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		10 10 07 07 —	2.84	2.84	1.91	1.91	—	9.5 (2.2–11.5)	2350 (460–2850)	10.76 (2.50–12.64)	54	69				
		13 10 07 07 —	3.37	2.69	1.82	1.82	—	9.7 (2.2–11.6)	2370 (470–2880)	10.85 (2.55–12.78)	54	69				
		16 10 07 07 —	3.62	2.63	1.78	1.78	—	9.8 (2.2–11.6)	2380 (480–2880)	10.89 (2.61–12.78)	54	69				
		18 10 07 07 —	3.86	2.57	1.74	1.74	—	9.9 (2.2–11.7)	2390 (480–2900)	10.94 (2.61–12.87)	54	69				
		22 10 07 07 —	4.27	2.44	1.65	1.65	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		24 10 07 07 —	4.63	2.29	1.54	1.54	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		13 13 07 07 —	3.21	3.21	1.74	1.74	—	9.9 (2.2–11.7)	2390 (480–2900)	10.94 (2.61–12.87)	54	69				
		16 13 07 07 —	3.46	3.14	1.70	1.70	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		18 13 07 07 —	3.66	3.05	1.65	1.65	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		22 13 07 07 —	4.02	2.87	1.55	1.55	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		24 13 07 07 —	4.38	2.70	1.46	1.46	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		16 16 07 07 —	3.35	3.35	1.65	1.65	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		18 16 07 07 —	3.55	3.25	1.60	1.60	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		22 16 07 07 —	3.91	3.07	1.51	1.51	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		24 16 07 07 —	4.26	2.89	1.42	1.42	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		18 18 07 07 —	3.45	3.45	1.55	1.55	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		22 18 07 07 —	3.80	3.26	1.47	1.47	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		24 18 07 07 —	4.15	3.08	1.38	1.38	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		10 10 10 07 —	2.61	2.61	2.61	1.76	—	9.6 (2.2–11.6)	2360 (470–2880)	10.80 (2.55–12.78)	54	69				
		13 10 10 07 —	3.12	2.50	2.50	1.69	—	9.8 (2.2–11.6)	2380 (480–2880)	10.89 (2.61–12.78)	54	69				
		16 10 10 07 —	3.36	2.44	2.44	1.65	—	9.9 (2.2–11.7)	2390 (480–2900)	10.94 (2.61–12.87)	54	69				
		18 10 10 07 —	3.59	2.40	2.40	1.62	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		22 10 10 07 —	3.95	2.26	2.26	1.53	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		24 10 10 07 —	4.31	2.13	2.13	1.44	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		13 13 10 07 —	2.99	2.99	2.40	1.62	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		16 13 10 07 —	3.20	2.91	2.33	1.57	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		18 13 10 07 —	3.39	2.82	2.26	1.53	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		22 13 10 07 —	3.74	2.67	2.14	1.44	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		24 13 10 07 —	4.09	2.53	2.02	1.36	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		16 16 10 07 —	3.11	3.11	2.26	1.53	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		18 16 10 07 —	3.30	3.02	2.20	1.48	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		22 16 10 07 —	3.65	2.86	2.08	1.41	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		24 16 10 07 —	3.99	2.71	1.97	1.33	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		18 18 10 07 —	3.21	3.21	2.14	1.44	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		22 18 10 07 —	3.55	3.05	2.03	1.37	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		24 18 10 07 —	3.89	2.88	1.92	1.30	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		13 13 13 07 —	2.82	2.82	2.82	1.53	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		16 13 13 07 —	3.02	2.75	2.75	1.48	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		18 13 13 07 —	3.21	2.67	2.67	1.44	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		22 13 13 07 —	3.55	2.54	2.54	1.37	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		24 13 13 07 —	3.89	2.40	2.40	1.30	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		16 16 13 07 —	2.94	2.94	2.67	1.44	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		18 16 13 07 —	3.13	2.86	2.60	1.41	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		22 16 13 07 —	3.47	2.72	2.48	1.34	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		24 16 13 07 —	3.80	2.58	2.35	1.27	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		18 18 13 07 —	3.05	3.05	2.54	1.37	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		22 18 13 07 —	3.38	2.90	2.42	1.30	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		24 18 13 07 —	3.72	2.75	2.29	1.24	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		10 10 10 10 —	2.43	2.43	2.43	2.43	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		13 10 10 10 —	2.91	2.33	2.33	2.33	—	9.9 (2.2–11.7)	2390 (480–2900)	10.94 (2.61–12.87)	54	69				
		16 10 10 10 —	3.14	2.29	2.29	2.29	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		18 10 10 10 —	3.33	2.22	2.22	2.22	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		22 10 10 10 —	3.68	2.11	2.11	2.11	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		24 10 10 10 —	4.03	1.99	1.99	1.99	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		13 13 10 10 —	2.78	2.78	2.22	2.22	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		16 13 10 10 —	2.97	2.70	2.16	2.16	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		22 13 10 10 —	3.50	2.50	2.00	2.00	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		24 13 10 10 —	3.84	2.37	1.90	1.90	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		16 16 10 10 —	2.89	2.89	2.11	2.11	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		18 13 10 10 —	3.16	2.63	2.11	2.11	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
		22 16 10 10 —	3.41	2.68	1.95	1.95	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69				
24 16 10 10 —	3.75	2.55	1.85	1.85	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69						
18 16 10 10 —	3.08	2.82	2.05	2.05	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69						
18 18 10 10 —	3.00	3.00	2.00	2.00	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69						
22 18 10 10 —	3.33	2.86	1.90	1.90	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69						
24 18 10 10 —	3.67	2.71	1.81	1.81	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69						
13 13 13 10 —	2.63	2.63	2.63	2.11	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69						
16 13 13 10 —	2.82	2.56	2.56	2.05	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69						
22 13 13 10 —	3.33	2.38	2.38	1.90	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69						
24 13 13 10 —	3.67	2.26	2.26	1.81	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69						
16 16 13 10 —	2.75	2.75	2.50	2.00	—	10.0 (2.2–11.7)	2400 (490–2900)	10.98 (2.66–12.87)	54	69						
22																

<Heating / 230V> (Continued)

Power supply (V)	Operating Status	Indoor unit					Unit Capacity					Total			Outdoor noise (dB)	
		A	B	C	D	E	A	B	C	D	E	Cooling capacity (kW)	Power consumption (W)	Operating current (A)	Sound Pressure	Sound Power
230	5 units	07	07	07	07	07	2.28	2.28	2.28	2.28	2.28	11.4 (3.4-13.4)	2690 (775-4020)	12.31 (4.21-17.83)	54	69
		10	07	07	07	07	3.16	2.13	2.13	2.13	2.13	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		13	07	07	07	07	3.70	2.00	2.00	2.00	2.00	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		16	07	07	07	07	3.95	1.94	1.94	1.94	1.94	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		18	07	07	07	07	4.18	1.88	1.88	1.88	1.88	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		10	10	07	07	07	2.91	2.91	1.96	1.96	1.96	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		13	10	07	07	07	3.42	2.74	1.85	1.85	1.85	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		16	10	07	07	07	3.66	2.66	1.79	1.79	1.79	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		18	10	07	07	07	3.88	2.59	1.75	1.75	1.75	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		13	13	07	07	07	3.23	3.23	1.75	1.75	1.75	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		16	13	07	07	07	3.46	3.15	1.70	1.70	1.70	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		18	13	07	07	07	3.68	3.06	1.65	1.65	1.65	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		16	16	07	07	07	3.37	3.37	1.65	1.65	1.65	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		18	16	07	07	07	3.58	3.28	1.61	1.61	1.61	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		10	10	10	07	07	2.69	2.69	2.69	1.82	1.82	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		13	10	10	07	07	3.18	2.54	2.54	1.72	1.72	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		13	13	10	07	07	3.02	3.02	2.41	1.63	1.63	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		16	10	10	07	07	3.40	2.48	2.48	1.67	1.67	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		18	10	10	07	07	3.62	2.41	2.41	1.63	1.63	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		13	13	13	07	07	2.87	2.87	2.87	1.55	1.55	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		16	13	13	07	07	3.08	2.80	2.80	1.51	1.51	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		18	13	13	07	07	3.28	2.73	2.73	1.48	1.48	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		16	16	10	07	07	3.15	3.15	2.29	1.55	1.55	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		18	16	10	07	07	3.36	3.08	2.24	1.51	1.51	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		16	16	13	07	07	3.01	3.01	2.73	1.48	1.48	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		18	16	13	07	07	3.21	2.94	2.67	1.44	1.44	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		10	10	10	10	10	2.50	2.50	2.50	2.50	1.69	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		13	10	10	10	10	2.97	2.38	2.38	2.38	1.60	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		16	10	10	10	10	3.19	2.32	2.32	2.32	1.56	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		18	10	10	10	10	3.39	2.26	2.26	2.26	1.53	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		13	13	10	10	10	2.83	2.83	2.26	2.26	1.53	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		16	13	10	10	10	3.04	2.76	2.21	2.21	1.49	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		18	13	10	10	10	3.24	2.70	2.16	2.16	1.46	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		16	16	10	10	10	2.97	2.97	2.16	2.16	1.46	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		13	13	13	10	10	2.70	2.70	2.70	2.16	1.46	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		16	13	13	10	10	2.90	2.64	2.64	2.11	1.42	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		16	16	13	10	10	2.83	2.83	2.58	2.06	1.39	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		13	13	13	13	07	2.58	2.58	2.58	2.58	1.39	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		16	13	13	13	07	2.77	2.52	2.52	2.52	1.36	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		16	16	13	13	13	2.72	2.72	2.47	2.47	1.33	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		10	10	10	10	10	2.34	2.34	2.34	2.34	2.34	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		13	10	10	10	10	2.79	2.23	2.23	2.23	2.23	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		16	10	10	10	10	2.99	2.18	2.18	2.18	2.18	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		18	10	10	10	10	3.19	2.13	2.13	2.13	2.13	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		13	13	10	10	10	2.66	2.66	2.13	2.13	2.13	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		16	13	10	10	10	2.86	2.60	2.08	2.08	2.08	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		18	13	10	10	10	3.05	2.54	2.03	2.03	2.03	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		16	16	10	10	10	2.80	2.80	2.03	2.03	2.03	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		13	13	13	10	10	2.54	2.54	2.54	2.03	2.03	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		16	13	13	10	10	2.74	2.49	2.49	1.99	1.99	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		18	13	13	10	10	2.93	2.44	2.44	1.95	1.95	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		16	16	13	10	10	2.75	2.75	2.50	2.00	2.00	12.0 (3.4-14.0)	2833 (775-4200)	12.97 (4.21-18.63)	54	69
		13	13	13	13	10	2.44	2.44	2.44	2.44	1.95	11.7 (3.4-13.7)	2762 (775-4120)	12.64 (4.21-18.28)	54	69
		16	13	13	13	10	2.69	2.45	2.45	2.45	1.96	12.0 (3.4-14.0)	2833 (775-4200)	12.97 (4.21-18.63)	54	69
		18	13	13	13	10	2.88	2.40	2.40	2.40	1.92	12.0 (3.4-14.0)	2833 (775-4200)	12.97 (4.21-18.63)	54	69
		16	16	13	13	10	2.64	2.64	2.40	2.40	1.92	12.0 (3.4-14.0)	2833 (775-4200)	12.97 (4.21-18.63)	54	69
		13	13	13	13	13	2.40	2.40	2.40	2.40	2.40	12.0 (3.4-14.0)	2833 (775-4200)	12.97 (4.21-18.63)	54	69
		16	13	13	13	13	2.59	2.35	2.35	2.35	2.35	12.0 (3.4-14.0)	2833 (775-4200)	12.97 (4.21-18.63)	54	69
		22	07*	07*	07*	07*	4.72	1.82	1.82	1.82	1.82	12.0 (3.4-14.0)	2833 (775-4200)	12.97 (4.21-18.63)	54	69
		22	10*	07*	07*	07*	4.40	2.51	1.70	1.70	1.70	12.0 (3.4-14.0)	2833 (775-4200)	12.97 (4.21-18.63)	54	69
		22	10*	10*	07*	07*	4.12	2.35	2.35	1.59	1.59	12.0 (3.4-14.0)	2833 (775-4200)	12.97 (4.21-18.63)	54	69
		22	10*	10*	10*	07*	3.87	2.21	2.21	2.21	1.49	12.0 (3.4-14.0)	2833 (775-4200)	12.97 (4.21-18.63)	54	69
		22	10*	10*	10*	10*	3.65	2.09	2.09	2.09	2.09	12.0 (3.4-14.0)	2833 (775-4200)	12.97 (4.21-18.63)	54	69
		22	13*	07*	07*	07*	4.18	2.99	1.61	1.61	1.61	12.0 (3.4-14.0)	2833 (775-4200)	12.97 (4.21-18.63)	54	69
		22	13*	10*	07*	07*	3.93	2.80	2.24	1.51	1.51	12.0 (3.4-14.0)	2833 (775-4200)	12.97 (4.21-18.63)	54	69
		22	13*	10*	10*	07*	3.70	2.64	2.11	2.11	1.43	12.0 (3.4-14.0)	2833 (775-4200)	12.97 (4.21-18.63)	54	69
		22	13*	10*	10*	10*	3.50	2.50	2.00	2.00	2.00	12.0 (3.4-14.0)	2833 (775-4200)	12.97 (4.21-18.63)	54	69
		22	13*	13*	07*	07*	3.75	2.68	2.68	1.45	1.45	12.0 (3.4-14.0)	2833 (775-4200)	12.97 (4.21-18.63)	54	69
		22	13*	13*	10*	07*	3.54	2.53	2.53	2.03	1.37	12.0 (3.4-14.0)	2833 (775-4200)	12.97 (4.21-18.63)	54	69
		22	13*	13*	10*	10*	3.36	2.40	2.40	1.92	1.92	12.0 (3.4-14.0)	2833 (775-4200)	12.97 (4.21-18.63)	54	69
22	13*	13*	13*	07*	3.40	2.43										

<Heating / 240V>

Power supply (V)	Operating Status	Indoor unit					Unit Capacity					Total			Outdoor noise (dB)	
		A	B	C	D	E	A	B	C	D	E	Cooling capacity (kW)	Power consumption (W)	Operating current (A)	Sound Pressure	Sound Power
240	1 unit	07	—	—	—	—	2.7	—	—	—	—	2.7 (0.8–4.8)	900 (300–1980)	4.31 (1.71–8.42)	54	69
		10	—	—	—	—	4.0	—	—	—	—	4.0 (0.8–5.2)	1450 (300–1980)	6.36 (1.71–8.42)	54	69
		13	—	—	—	—	5.0	—	—	—	—	5.0 (0.8–6.5)	2050 (310–2750)	8.99 (1.77–11.69)	54	69
		16	—	—	—	—	5.5	—	—	—	—	5.5 (0.8–6.9)	2400 (310–3000)	10.53 (1.77–12.76)	54	69
		18	—	—	—	—	6.0	—	—	—	—	6.0 (0.8–7.1)	2630 (310–3200)	11.54 (1.77–13.61)	54	69
		22	—	—	—	—	7.0	—	—	—	—	7.0 (1.8–8.2)	2700 (330–3600)	11.72 (1.88–15.31)	54	69
		24	—	—	—	—	8.1	—	—	—	—	8.1 (1.8–8.6)	3300 (330–3700)	14.32 (1.88–15.73)	54	69
		07	07	—	—	—	2.70	2.70	—	—	—	5.4 (1.5–7.4)	2050 (320–3200)	8.99 (1.78–13.61)	54	69
		10	07	—	—	—	4.00	2.70	—	—	—	6.7 (1.5–8.9)	2080 (320–3200)	9.12 (1.78–13.61)	54	69
		13	07	—	—	—	4.81	2.59	—	—	—	7.4 (1.5–10.1)	2320 (320–3210)	10.18 (1.78–13.65)	54	69
	2 units	16	07	—	—	—	5.10	2.50	—	—	—	7.6 (1.5–10.1)	2480 (320–3230)	10.88 (1.78–13.73)	54	69
		18	07	—	—	—	5.45	2.45	—	—	—	7.9 (1.5–10.1)	2480 (320–3230)	10.88 (1.78–13.73)	54	69
		22	07	—	—	—	5.70	2.20	—	—	—	7.9 (1.5–10.1)	2480 (320–3230)	10.88 (1.78–13.73)	54	69
		24	07	—	—	—	6.23	2.08	—	—	—	8.3 (1.5–10.2)	2700 (320–3240)	11.84 (1.78–13.78)	54	69
		10	10	—	—	—	3.60	3.60	—	—	—	7.2 (1.5–10.0)	2100 (320–3200)	9.21 (1.78–13.61)	54	69
		13	10	—	—	—	4.22	3.38	—	—	—	7.6 (1.5–10.1)	2320 (320–3210)	10.18 (1.78–13.65)	54	69
		16	10	—	—	—	4.57	3.33	—	—	—	7.9 (1.5–10.1)	2480 (320–3230)	10.88 (1.78–13.73)	54	69
		18	10	—	—	—	4.74	3.16	—	—	—	7.9 (1.5–10.1)	2480 (320–3230)	10.88 (1.78–13.73)	54	69
		22	10	—	—	—	5.28	3.02	—	—	—	8.3 (1.5–10.2)	2700 (320–3240)	11.84 (1.78–13.78)	54	69
		24	10	—	—	—	5.76	2.84	—	—	—	8.6 (1.5–10.2)	2860 (320–3250)	12.54 (1.78–13.82)	54	69
		13	13	—	—	—	3.95	3.95	—	—	—	7.9 (1.5–10.1)	2480 (320–3230)	10.88 (1.78–13.73)	54	69
		16	13	—	—	—	4.35	3.95	—	—	—	8.3 (1.5–10.2)	2700 (320–3240)	11.84 (1.78–13.78)	54	69
		18	13	—	—	—	4.53	3.77	—	—	—	8.3 (1.5–10.2)	2700 (320–3240)	11.84 (1.78–13.78)	54	69
		22	13	—	—	—	5.02	3.58	—	—	—	8.6 (1.5–10.2)	2860 (320–3250)	12.54 (1.78–13.82)	54	69
		24	13	—	—	—	5.32	3.28	—	—	—	8.6 (1.5–10.2)	2860 (320–3250)	12.54 (1.78–13.82)	54	69
		16	16	—	—	—	4.30	4.30	—	—	—	8.6 (1.5–10.2)	2860 (320–3250)	12.54 (1.78–13.82)	54	69
		18	16	—	—	—	4.49	4.11	—	—	—	8.6 (1.5–10.2)	2860 (320–3250)	12.54 (1.78–13.82)	54	69
		22	16	—	—	—	4.82	3.78	—	—	—	8.6 (1.5–10.2)	2860 (320–3250)	12.54 (1.78–13.82)	54	69
		24	16	—	—	—	5.12	3.48	—	—	—	8.6 (1.5–10.2)	2860 (320–3250)	12.54 (1.78–13.82)	54	69
		18	18	—	—	—	4.30	4.30	—	—	—	8.6 (1.5–10.2)	2860 (320–3250)	12.54 (1.78–13.82)	54	69
		22	18	—	—	—	4.63	3.97	—	—	—	8.6 (1.5–10.2)	2860 (320–3250)	12.54 (1.78–13.82)	54	69
		24	18	—	—	—	4.94	3.66	—	—	—	8.6 (1.5–10.2)	2860 (320–3250)	12.54 (1.78–13.82)	54	69
		22	22	—	—	—	4.50	4.50	—	—	—	9.0 (1.5–10.6)	2200 (320–2590)	9.55 (1.78–11.01)	54	69
		22	24	—	—	—	4.17	4.83	—	—	—	9.0 (1.5–10.6)	2200 (320–2590)	9.55 (1.78–11.01)	54	69
		24	24	—	—	—	4.55	4.55	—	—	—	9.1 (1.5–10.7)	2220 (320–2610)	9.64 (1.78–11.10)	54	69
	3 units	07	07	07	—	—	2.70	2.70	2.70	—	—	8.1 (2.0–10.4)	2290 (380–2750)	10.04 (1.98–11.69)	54	69
		10	07	07	—	—	3.53	2.38	2.38	—	—	8.3 (2.0–10.4)	2300 (380–2750)	10.09 (1.98–11.69)	54	69
		13	07	07	—	—	4.13	2.23	2.23	—	—	8.6 (2.0–10.4)	2300 (380–2750)	10.09 (1.98–11.69)	54	69
		16	07	07	—	—	4.39	2.16	2.16	—	—	8.7 (2.0–10.5)	2350 (380–2760)	10.31 (1.98–11.73)	54	69
		18	07	07	—	—	4.58	2.06	2.06	—	—	8.7 (2.0–10.5)	2350 (380–2760)	10.31 (1.98–11.73)	54	69
		22	07	07	—	—	4.91	1.89	1.89	—	—	8.7 (2.0–10.5)	2350 (380–2760)	10.31 (1.98–11.73)	54	69
		24	07	07	—	—	5.22	1.74	1.74	—	—	8.7 (2.0–10.5)	2350 (380–2760)	10.31 (1.98–11.73)	54	69
		10	10	07	—	—	3.18	3.18	2.14	—	—	8.5 (2.0–10.4)	2300 (380–2750)	10.09 (1.98–11.69)	54	69
		13	10	07	—	—	3.72	2.97	2.01	—	—	8.7 (2.0–10.5)	2350 (380–2760)	10.31 (1.98–11.73)	54	69
		16	10	07	—	—	3.92	2.85	1.93	—	—	8.7 (2.0–10.5)	2350 (380–2760)	10.31 (1.98–11.73)	54	69
		18	10	07	—	—	4.11	2.74	1.85	—	—	8.7 (2.0–10.5)	2350 (380–2760)	10.31 (1.98–11.73)	54	69
		22	10	07	—	—	4.50	2.57	1.73	—	—	8.8 (2.0–10.6)	2400 (380–2780)	10.53 (1.98–11.82)	54	69
		24	10	07	—	—	4.82	2.38	1.61	—	—	8.8 (2.0–10.6)	2400 (380–2780)	10.53 (1.98–11.82)	54	69
		13	13	07	—	—	3.43	3.43	1.85	—	—	8.7 (2.0–10.5)	2350 (380–2760)	10.31 (1.98–11.73)	54	69
		16	13	07	—	—	3.67	3.33	1.80	—	—	8.8 (2.0–10.6)	2400 (380–2780)	10.53 (1.98–11.82)	54	69
		18	13	07	—	—	3.85	3.21	1.73	—	—	8.8 (2.0–10.6)	2400 (380–2780)	10.53 (1.98–11.82)	54	69
		22	13	07	—	—	4.24	3.03	1.63	—	—	8.9 (2.0–10.7)	2450 (380–2790)	10.75 (1.98–11.86)	54	69
		24	13	07	—	—	4.56	2.82	1.52	—	—	8.9 (2.0–10.7)	2450 (380–2790)	10.75 (1.98–11.86)	54	69
		16	16	07	—	—	3.57	3.57	1.75	—	—	8.9 (2.0–10.7)	2450 (380–2790)	10.75 (1.98–11.86)	54	69
		18	16	07	—	—	3.76	3.45	1.69	—	—	8.9 (2.0–10.7)	2450 (380–2790)	10.75 (1.98–11.86)	54	69
		22	16	07	—	—	4.10	3.22	1.58	—	—	8.9 (2.0–10.7)	2450 (380–2790)	10.75 (1.98–11.86)	54	69
		24	16	07	—	—	4.42	3.00	1.47	—	—	8.9 (2.0–10.7)	2450 (380–2790)	10.75 (1.98–11.86)	54	69
		18	18	07	—	—	3.63	3.63	1.63	—	—	8.9 (2.0–10.7)	2450 (380–2790)	10.75 (1.98–11.86)	54	69
		22	18	07	—	—	3.97	3.40	1.53	—	—	8.9 (2.0–10.7)	2450 (380–2790)	10.75 (1.98–11.86)	54	69
		24	18	07	—	—	4.29	3.18	1.43	—	—	8.9 (2.0–10.7)	2450 (380–2790)	10.75 (1.98–11.86)	54	69
		10	10	10	—	—	2.87	2.87	2.87	—	—	8.6 (2.0–10.4)	2300 (380–2750)	10.09 (1.98–11.69)	54	69
		13	10	10	—	—	3.35	2.68	2.68	—	—	8.7 (2.0–10.5)	2350 (380–2760)	10.31 (1.98–11.73)	54	69
		16	10	10	—	—	3.54	2.58	2.58	—	—	8.7 (2.0–10.5)	2350 (380–2760)	10.31 (1.98–11.73)	54	69
		18	10	10	—	—	3.73	2.49	2.49	—	—	8.7 (2.0–10.5)	2350 (380–2760)	10.31 (1.98–11.73)	54	69
		22	10	10	—	—	4.15	2.37	2.37	—	—	8.9 (2.0–10.7)	2450 (380–2790)	10.75 (1.98–11.86)	54	69
		24	10	10	—	—	4.48	2.21	2.21	—	—	8.9 (2.0–10.7)	2450 (380–2790)	10.75 (1.98–11.86)	54	69
		13	13	10	—	—	3.11	3.11	2.49	—	—	8.7 (2.0–10.5)	2350 (380–2760)	10.31 (1.98–11.73)	54	69
		16	13	10	—	—	3.34	3.03	2.43	—	—	8.8 (2.0–10.6)	2400 (380–2780)	10.53 (1.98–11.82)	54	69
		18	13	10	—	—	3.56	2.97	2.37	—	—	8.9 (2.0–10.7)	2450 (380–2790)	10.75 (1.98–11.86)	54	69
		22	13	10	—	—	3.89	2.78	2.23	—	—	8.9 (2.0–10.7)	2450 (380–2790)	10.75 (1.98–11.86)	54	69
		24	13	10	—	—	4.22	2.60	2.08	—	—	8.9 (2.0–10.7)	2450 (380–2790)	10.75 (1.98–11.86)	54	69
		16	16	10	—	—	3.26	3.26	2.37	—	—	8.9 (2.0–10.7)	2450 (380–2790)	10.75 (1.98–11.86)	54	69
		18	16	10	—	—	3.45	3.16	2.30	—	—	8.9 (2.0–10.7)	2450 (380–2790)	10.75 (1.98–11.86)	54	69
		22	16	10	—	—	3.78	2.97	2.16	—	—	8.9 (2.0–10.7)	2450 (380–2790)	10.75 (1.98–11.86)	54	69
24		16	10	—	—	4.10	2.78	2.02	—	—	8.9 (2.0–10.7)	2450 (380–2790)	10.75 (1.98–11.86)	54	69	
18		18	10	—	—	3.34	3.34	2.23	—	—	8.9 (2.0–10.7)	2450 (380–2				

<Heating / 240V> (Continued)

Power supply (V)	Operating Status	Indoor unit					Unit Capacity					Total					Outdoor noise (dB)	
		A	B	C	D	E	A	B	C	D	E	Cooling capacity (kW)	Power consumption (W)	Operating current (A)	Sound Pressure	Sound Power		
240	4 units	07	07	07	07	—	2.33	2.33	2.33	2.33	—	9.3 (2.2-11.5)	2330 (450-2850)	10.22 (2.34-12.12)	54	69		
		10	07	07	07	—	3.11	2.10	2.10	2.10	—	9.4 (2.2-11.5)	2340 (460-2850)	10.26 (2.40-12.12)	54	69		
		13	07	07	07	—	3.66	1.98	1.98	1.98	—	9.6 (2.2-11.6)	2360 (470-2860)	10.35 (2.45-12.16)	54	69		
		16	07	07	07	—	3.92	1.93	1.93	1.93	—	9.7 (2.2-11.6)	2370 (470-2880)	10.39 (2.45-12.24)	54	69		
		18	07	07	07	—	4.17	1.88	1.88	1.88	—	9.8 (2.2-11.6)	2380 (480-2880)	10.44 (2.50-12.24)	54	69		
		22	07	07	07	—	4.64	1.79	1.79	1.79	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		24	07	07	07	—	5.00	1.67	1.67	1.67	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		10	10	07	07	—	2.84	2.84	1.91	1.91	—	9.5 (2.2-11.5)	2350 (460-2850)	10.31 (2.40-12.12)	54	69		
		13	10	07	07	—	3.37	2.69	1.82	1.82	—	9.7 (2.2-11.6)	2370 (470-2880)	10.39 (2.45-12.24)	54	69		
		16	10	07	07	—	3.62	2.63	1.78	1.78	—	9.8 (2.2-11.6)	2380 (480-2880)	10.44 (2.50-12.24)	54	69		
		18	10	07	07	—	3.86	2.57	1.74	1.74	—	9.9 (2.2-11.7)	2390 (480-2900)	10.48 (2.50-12.33)	54	69		
		22	10	07	07	—	4.27	2.44	1.65	1.65	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		24	10	07	07	—	4.63	2.29	1.54	1.54	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		13	13	07	07	—	3.21	3.21	1.74	1.74	—	9.9 (2.2-11.7)	2390 (480-2900)	10.48 (2.50-12.33)	54	69		
		16	13	07	07	—	3.46	3.14	1.70	1.70	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		18	13	07	07	—	3.66	3.05	1.65	1.65	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		22	13	07	07	—	4.02	2.87	1.55	1.55	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		24	13	07	07	—	4.38	2.70	1.46	1.46	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		16	16	07	07	—	3.35	3.35	1.65	1.65	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		18	16	07	07	—	3.55	3.25	1.60	1.60	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		22	16	07	07	—	3.91	3.07	1.51	1.51	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		24	16	07	07	—	4.26	2.89	1.42	1.42	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		18	18	07	07	—	3.45	3.45	1.55	1.55	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		22	18	07	07	—	3.80	3.26	1.47	1.47	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		24	18	07	07	—	4.15	3.08	1.38	1.38	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		10	10	10	07	—	2.61	2.61	2.61	1.76	—	9.6 (2.2-11.6)	2360 (470-2880)	10.35 (2.45-12.24)	54	69		
		13	10	10	07	—	3.12	2.50	2.50	1.69	—	9.8 (2.2-11.6)	2380 (480-2880)	10.44 (2.50-12.24)	54	69		
		16	10	10	07	—	3.36	2.44	2.44	1.65	—	9.9 (2.2-11.7)	2390 (480-2900)	10.48 (2.50-12.33)	54	69		
		18	10	10	07	—	3.59	2.40	2.40	1.62	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		22	10	10	07	—	3.95	2.26	2.26	1.53	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		24	10	10	07	—	4.31	2.13	2.13	1.44	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		13	13	10	07	—	2.99	2.99	2.40	1.62	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		16	13	10	07	—	3.20	2.91	2.33	1.57	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		18	13	10	07	—	3.39	2.82	2.26	1.53	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		22	13	10	07	—	3.74	2.67	2.14	1.44	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		24	13	10	07	—	4.09	2.53	2.02	1.36	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		16	16	10	07	—	3.11	3.11	2.26	1.53	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		18	16	10	07	—	3.30	3.02	2.20	1.48	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		22	16	10	07	—	3.65	2.86	2.08	1.41	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		24	16	10	07	—	3.99	2.71	1.97	1.33	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		18	18	10	07	—	3.21	3.21	2.14	1.44	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		22	18	10	07	—	3.55	3.05	2.03	1.37	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		24	18	10	07	—	3.89	2.88	1.92	1.30	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		13	13	13	07	—	2.82	2.82	2.82	1.53	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		16	13	13	07	—	3.02	2.75	2.75	1.48	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		18	13	13	07	—	3.21	2.67	2.67	1.44	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		22	13	13	07	—	3.55	2.54	2.54	1.37	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		24	13	13	07	—	3.89	2.40	2.40	1.30	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		16	16	13	07	—	2.94	2.94	2.67	1.44	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		18	16	13	07	—	3.13	2.86	2.60	1.41	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		22	16	13	07	—	3.47	2.72	2.48	1.34	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		24	16	13	07	—	3.80	2.58	2.35	1.27	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		18	18	13	07	—	3.05	3.05	2.54	1.37	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		22	18	13	07	—	3.38	2.90	2.42	1.30	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		24	18	13	07	—	3.72	2.75	2.29	1.24	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		10	10	10	10	—	2.43	2.43	2.43	2.43	—	9.7 (2.2-11.6)	2370 (470-2780)	10.39 (2.45-11.82)	54	69		
		13	10	10	10	—	2.91	2.33	2.33	2.33	—	9.9 (2.2-11.7)	2390 (480-2900)	10.48 (2.50-12.33)	54	69		
		16	10	10	10	—	3.14	2.29	2.29	2.29	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		18	10	10	10	—	3.33	2.22	2.22	2.22	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		22	10	10	10	—	3.68	2.11	2.11	2.11	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		24	10	10	10	—	4.03	1.99	1.99	1.99	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		13	13	10	10	—	2.78	2.78	2.22	2.22	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		16	13	10	10	—	2.97	2.70	2.16	2.16	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		22	13	10	10	—	3.50	2.50	2.00	2.00	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		24	13	10	10	—	3.84	2.37	1.90	1.90	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		16	16	10	10	—	2.89	2.89	2.11	2.11	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
		18	13	10	10	—	3.16	2.63	2.11	2.11	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69		
22	16	10	10	—	3.41	2.68	1.95	1.95	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69				
24	16	10	10	—	3.75	2.55	1.85	1.85	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69				
18	16	10	10	—	3.08	2.82	2.05	2.05	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69				
18	18	10	10	—	3.00	3.00	2.00	2.00	—	10.0 (2.2-11.7)	2400 (490-2900)	10.53 (2.55-12.33)	54	69				
22	18	10	10	—	3.33	2.												

<Heating / 240V> (Continued)

Power supply (V)	Operating Status	Indoor unit					Unit Capacity					Total			Outdoor noise (dB)	
		A	B	C	D	E	A	B	C	D	E	Cooling capacity (kW)	Power consumption (W)	Operating current (A)	Sound Pressure	Sound Power
240	5 units	07	07	07	07	07	2.28	2.28	2.28	2.28	2.28	11.4 (3.4-13.4)	2690 (775-4020)	11.80 (4.04-17.09)	54	69
		10	07	07	07	07	3.16	2.13	2.13	2.13	2.13	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		13	07	07	07	07	3.70	2.00	2.00	2.00	2.00	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		16	07	07	07	07	3.95	1.94	1.94	1.94	1.94	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		18	07	07	07	07	4.18	1.88	1.88	1.88	1.88	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		10	10	07	07	07	2.91	2.91	1.96	1.96	1.96	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		13	10	07	07	07	3.42	2.74	1.85	1.85	1.85	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		16	10	07	07	07	3.66	2.66	1.79	1.79	1.79	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		18	10	07	07	07	3.88	2.59	1.75	1.75	1.75	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		13	13	07	07	07	3.23	3.23	1.75	1.75	1.75	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		16	13	07	07	07	3.46	3.15	1.70	1.70	1.70	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		18	13	07	07	07	3.68	3.06	1.65	1.65	1.65	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		16	16	07	07	07	3.37	3.37	1.65	1.65	1.65	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		18	16	07	07	07	3.58	3.28	1.61	1.61	1.61	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		10	10	10	07	07	2.69	2.69	2.69	1.82	1.82	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		13	10	10	07	07	3.18	2.54	2.54	1.72	1.72	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		13	13	10	07	07	3.02	3.02	2.41	1.63	1.63	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		16	10	10	07	07	3.40	2.48	2.48	1.67	1.67	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		18	10	10	07	07	3.62	2.41	2.41	1.63	1.63	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		13	13	13	07	07	2.87	2.87	2.87	1.55	1.55	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		16	13	13	07	07	3.08	2.80	2.80	1.51	1.51	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		18	13	13	07	07	3.28	2.73	2.73	1.48	1.48	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		16	16	10	07	07	3.15	3.15	2.29	1.55	1.55	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		18	16	10	07	07	3.36	3.08	2.24	1.51	1.51	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		16	16	13	07	07	3.01	3.01	2.73	1.48	1.48	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		18	16	13	07	07	3.21	2.94	2.67	1.44	1.44	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		10	10	10	10	07	2.50	2.50	2.50	2.50	1.69	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		13	10	10	10	07	2.97	2.38	2.38	2.38	1.60	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		16	10	10	10	07	3.19	2.32	2.32	2.32	1.56	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		18	10	10	10	07	3.39	2.26	2.26	2.26	1.53	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		13	13	10	10	07	2.83	2.83	2.26	2.26	1.53	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		16	13	10	10	07	3.04	2.76	2.21	2.21	1.49	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		18	13	10	10	07	3.24	2.70	2.16	2.16	1.46	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		16	16	10	10	07	2.97	2.97	2.16	2.16	1.46	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		13	13	13	10	07	2.70	2.70	2.70	2.16	1.46	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		16	13	13	10	07	2.90	2.64	2.64	2.11	1.42	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		16	16	13	10	07	2.83	2.83	2.58	2.06	1.39	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		13	13	13	13	07	2.58	2.58	2.58	2.58	1.39	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		16	13	13	13	07	2.77	2.52	2.52	2.52	1.36	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		16	16	13	13	07	2.72	2.72	2.47	2.47	1.33	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		10	10	10	10	10	2.34	2.34	2.34	2.34	2.34	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		13	10	10	10	10	2.79	2.23	2.23	2.23	2.23	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		16	10	10	10	10	2.99	2.18	2.18	2.18	2.18	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		18	10	10	10	10	3.19	2.13	2.13	2.13	2.13	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		13	13	10	10	10	2.66	2.66	2.13	2.13	2.13	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		16	13	10	10	10	2.86	2.60	2.08	2.08	2.08	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		18	13	10	10	10	3.05	2.54	2.03	2.03	2.03	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		16	16	10	10	10	2.80	2.80	2.03	2.03	2.03	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		13	13	13	10	10	2.54	2.54	2.54	2.03	2.03	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		16	13	13	10	10	2.74	2.49	2.49	1.99	1.99	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		18	13	13	10	10	2.93	2.44	2.44	1.95	1.95	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		16	16	13	10	10	2.75	2.75	2.50	2.00	2.00	12.0 (3.4-14.0)	2833 (775-4200)	12.43 (4.04-17.86)	54	69
		13	13	13	13	10	2.44	2.44	2.44	2.44	1.95	11.7 (3.4-13.7)	2762 (775-4120)	12.11 (4.04-17.52)	54	69
		16	13	13	13	10	2.69	2.45	2.45	2.45	1.96	12.0 (3.4-14.0)	2833 (775-4200)	12.43 (4.04-17.86)	54	69
		18	13	13	13	10	2.88	2.40	2.40	2.40	1.92	12.0 (3.4-14.0)	2833 (775-4200)	12.43 (4.04-17.86)	54	69
		16	16	13	13	10	2.64	2.64	2.40	2.40	1.92	12.0 (3.4-14.0)	2833 (775-4200)	12.43 (4.04-17.86)	54	69
		13	13	13	13	13	2.40	2.40	2.40	2.40	2.40	12.0 (3.4-14.0)	2833 (775-4200)	12.43 (4.04-17.86)	54	69
		16	13	13	13	13	2.59	2.35	2.35	2.35	2.35	12.0 (3.4-14.0)	2833 (775-4200)	12.43 (4.04-17.86)	54	69
		22	07*	07*	07*	07*	4.72	1.82	1.82	1.82	1.82	12.0 (3.4-14.0)	2833 (775-4200)	12.43 (4.04-17.86)	54	69
		22	10*	07*	07*	07*	4.40	2.51	1.70	1.70	1.70	12.0 (3.4-14.0)	2833 (775-4200)	12.43 (4.04-17.86)	54	69
		22	10*	10*	07*	07*	4.12	2.35	2.35	1.59	1.59	12.0 (3.4-14.0)	2833 (775-4200)	12.43 (4.04-17.86)	54	69
		22	10*	10*	10*	07*	3.87	2.21	2.21	2.21	1.49	12.0 (3.4-14.0)	2833 (775-4200)	12.43 (4.04-17.86)	54	69
		22	10*	10*	10*	10*	3.65	2.09	2.09	2.09	2.09	12.0 (3.4-14.0)	2833 (775-4200)	12.43 (4.04-17.86)	54	69
		22	13*	07*	07*	07*	4.18	2.99	1.61	1.61	1.61	12.0 (3.4-14.0)	2833 (775-4200)	12.43 (4.04-17.86)	54	69
		22	13*	10*	07*	07*	3.93	2.80	2.24	1.51	1.51	12.0 (3.4-14.0)	2833 (775-4200)	12.43 (4.04-17.86)	54	69
		22	13*	10*	10*	07*	3.70	2.64	2.11	2.11	1.43	12.0 (3.4-14.0)	2833 (775-4200)	12.43 (4.04-17.86)	54	69
		22	13*	10*	10*	10*	3.50	2.50	2.00	2.00	2.00	12.0 (3.4-14.0)	2833 (775-4200)	12.43 (4.04-17.86)	54	69
		22	13*	13*	07*	07*	3.75	2.68	2.68	1.45	1.45	12.0 (3.4-14.0)	2833 (775-4200)	12.43 (4.04-17.86)	54	69
		22	13*	13*	10*	07*	3.54	2.53	2.53	2.03	1.37	12.0 (3.4-14.0)	2833 (775-4200)	12.43 (4.04-17.86)	54	69
		22	13*	13*	10*	10*	3.36	2.40	2.40	1.92	1.92	12.0 (3.4-14.0)	2833 (775-4200)	12.43 (4.04-17.86)	54	69
22	13*	13*	13*	07*	3.40	2.43	2.43									